# Product Environmental Aspects **Declaration**

EP and IJ printer (PCR number: AD-04)



No. AD-12-194 Date of publication Jul./4/2012



# http://www.brother.co.jp/

For inquiry:

Environmental Product Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2406 FAX: +81-52-824-5667

# Black & White Laser Printer HL-5450DN Specifications:

- Electrophotographic Printer (EP)
- Black & White
- Printing Speed: 38ppm Maximum Printing Size: A4
- Duplex Printing

The following data is calculated by assuming the product prints 866,400 sheets in 5-year usage period. < Main environmental impact in the product lifecycle >


- 21.800MJ
- Energy consumption Global warming impact (CO<sub>2</sub> equivalent)

1,210.8kg

Acidification impact (SO<sub>2</sub> equivalent)

1.82ka





- Electric power consumption in 5 years of "Use stage" is 565kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR:Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf\_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

# [Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025 🗆 internal 🔳 external Third party verifier \*: System auditor, Shozo Nakamuta

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

<sup>\*</sup> In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

## Product Environmental Information Data Sheet (PEIDS)



Decument central ne	E 024 a 02
Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AD-12-194

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	EP and IJ printer		Product type	HL-5450DN				
PCR code	AD-04	Product weight (kg)	10.5	Package (kg)	2.0	Weight total (kg)	12.5	

Life Cycle Stage In/Out items						Produ	ıction	51 / 11 /		·	<b>-</b>
In/Out	t items				Unit	Raw material	Product	Distribution	Use	Disposal	Total
		Fnera	v Cons	umption	MJ	1.38E+03	1.27E+02	3.56E+01	2.03E+04	1.17E+01	2.18E+04
				,	Mcal	3.28E+02	3.03E+01	8.50E+00	4.84E+03	2.79E+00	5.21E+03
			≥ es	Coal	kg	6.93E+00	8.15E-01	8.32E-05	9.86E+01	7.04E-02	1.06E+02
			l gie	Crude oil (for fuel)	kg	1.36E+01	1.06E+00	7.78E-01	1.79E+02	1.25E-01	1.95E+02
			Energy resources	LNG	kg	2.86E+00	4.26E-01	1.20E-02	3.96E+01	3.62E-02	4.29E+01
			_ ē	Uranium content of an ore	kg	2.78E-04	5.51E-05	5.64E-09	4.33E-03	4.76E-06	4.67E-03
				Crude oil (for material)	kg	6.36E+00	3.53E-03	0	7.79E+01	0	8.42E+01
		"		Iron content of an ore	kg	3.24E+00	0	0	3.69E+01	0	4.01E+01
		Ses		Cu content of an ore	kg	1.95E-01	0	0	1.18E-01	0	3.13E-01
	Se	ū		Al content of an ore	kg	1.20E-01	0	0	1.62E+00	0	1.74E+00
	Impact by Resource Consumption	esc	ω	Ni content of an ore	kg	1.09E-02	0	0	1.46E-01	0	1.57E-01
	esc	9	Se	Cr content of an ore	kg	1.58E-02	0	0	2.10E-01	0	2.26E-01
	R M	iplo	l nc	Mn content of an ore	kg	1.65E-02	0	0	2.17E-01	0	2.34E-01
	by Isu	nst	esc	Pb content of an ore	kg	8.96E-03	0	0	4.33E-03	0	1.33E-02
	eact by Resou Consumption	Exhaustible resources	Mineral resources	Sn content of an ore	kg	-	ı	-	ı	-	
	ng O	Ë	iera	Zn content of an ore	kg	8.83E-02	0	0	4.27E-02	0	1.31E-01
	=		lÿ	Au content of an ore	kg	-	-	-	-	-	
			_	Ag content of an ore	kg	-	ı	-	-	-	
			enewable	Silica Sand	kg	2.84E-01	0	0	6.23E-01	0	9.07E-01
Inventory anaiyses				Halite	kg	1.81E+00	1.06E-04	0	6.46E+00	3.79E-03	8.27E+00
				Limestone	kg	8.46E-01	6.89E-03	0	9.74E+00	9.70E-02	1.07E+01
na				Natural soda ash	kg	2.47E-02	0	0	2.03E-02	0	4.50E-02
a		Rene	wable	Wood	kg	3.32E+00	2.07E-01	0	1.43E+02	0	1.47E+02
9		resou	urces	Water	kg	7.01E+03	6.29E+02	6.29E-02	6.77E+04	5.95E+01	7.54E+04
Ę				CO2	kg	6.97E+01	6.99E+00	2.53E+00	1.10E+03	1.05E+01	1.19E+03
Š				SOx	kg	4.43E-02	5.06E-03	1.46E-03	6.79E-01	5.49E-03	7.36E-01
				NOx	kg	9.07E-02	5.13E-03	1.07E-02	1.43E+00	1.17E-02	1.55E+00
			•	N2O	kg	6.49E-03	2.04E-04	4.43E-04	6.54E-02	1.56E-05	7.25E-02
	<u>e</u>	\tmoo		CH4	kg	7.43E-04	1.47E-04	1.51E-08	1.16E-02	1.27E-05	1.25E-02
	arç	Atmosphere		CO	kg	8.65E-03	1.05E-03	2.52E-03	2.05E-01	2.15E-03	2.19E-01
	t ch			NMVOC	kg	1.45E-03	2.89E-04	2.95E-08	2.26E-02	2.49E-05	2.44E-02
	Dis			CxHy	kg	3.05E-03	6.22E-05	3.40E-04	3.29E-02	4.10E-05	3.63E-02
	l/nc			Dust	kg	9.50E-03	2.85E-04	1.05E-03	1.16E-01	6.69E-04	1.28E-01
	ssic			BOD	kg	-	-	-	-	-	
	by Emission/Discharge the environment			COD	kg	-	-	-	_	-	
		-	0 .	N total	kg	-	-	-	_	-	
	t by	water	domain	P total	kg	-	-	-	_	-	
	Impact by to th			SS	kg	-	-	-	-	-	
	nps			Unspecified Solid Waste	kg	5.57E-01	2.58E-03	0	6.48E+01	4.74E+00	7.01E+01
	=			Slag	kg	1.14E+00	0	0	1.13E+01	0	1.24E+01
		to	О	Sludge	kg	1.77E-01	0	0	3.42E+00	0	3.59E+00
		Soil s	ystem								
			•	Low level	kg	1.95E-04	3.85E-05	3.94E-09	3.02E-03	3.32E-06	3.26E-03
				radio-active waste	,						
	0.5			Energy resources							
	tior			(crude oil equivalent)	kg	2.38E+01	2.55E+00	7.92E-01	3.26E+02	2.53E-01	3.53E+02
	by Resource Consumption		ustible	(crude oii equivalent)							
_	Re	resou	urces	Mineral resources							
en t	රිරි			(Iron ore equivalent)	kg	5.88E+01	1.94E-03	0	2.27E+02	0	2.86E+02
act				()							
Impact assessment	rrge			Global Warming							
- L	cha			(CO2 equivalent)	kg	7.15E+01	7.05E+00	2.65E+00	1.12E+03	1.05E+01	1.21E+03
ŭ	ct b Disr	to	0	(OOL equivalent)							
	Impact by Emission/Discharge to the environment	Atmos	sphere	A 1 100 ct							
	In lissi the			Acidification	kg	1.08E-01	8.64E-03	8.93E-03	1.68E+00	1.37E-02	1.82E+00
	Em to:			(SO2 equivalent)	.5						

## [Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage. C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel. C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.

  B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

  C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

## [Notes for readers: Target product specific]

- 1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photoreceptor, as well as the impact of product assembly
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance The transportation distance in Japan uses 100 km as average distance
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 866,400 sheets, calculated by supposing a user use a machine for 5 years.
- It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure. The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

- The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance
- Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.
- 5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines

# **Product data sheet**

Input data and parameters for I CA)

	(Input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AD-12-194



PCR name	EP and IJ printer(PCR ID:AD-04)	Product type	HL-5450DN				
LCA/LCIA in units of:	1	Product weight (kg)	10.5	Package (kg)	2.0	Weight total (kg)	12.5

1. Product information (per unit): parts etc. by material and by process/assembly method

		Breakdown of p	rimary materials		Math breakdown of parts, which	ch need to apply	Processing / Assembly Base Ur	nits (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	2.66E+00	Paper	1.55E+00	Press molding: Iron (kg)	2.73E+00	Parts assembly (kg)	1.80E+00
	Stainless steel	6.89E-02	Semiconductor substrate	8.00E-01	Press molding: Nonferrous metal (kg)	7.79E-02		
ಕ	Aluminum	7.79E-02	Wood	0	Injection molding (kg)	6.74E+00		
про	Other metal	0	Medium-sized motor	4.26E-01	Glass molding (kg)	5.74E-02		
풉	Thermoplastic resin	6.61E+00	Lubricants	4.65E-03				
	Thermosetting resin	4.50E-03						
	Rubber	2.23E-01						
	Glass	5.74E-02						
	Subtotal	9.70E+00	Subtotal	2.78E+00				
		Total				9.61E+00	Subtotal	1.80E+00
MI-A-								

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Energy
_	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 10 ton (kg.km)	Diesel truck: 2 ton (kg.km)	LNG as fuel (kg)	Diesel oil as fuel (kg)	Heavy oil fuel (kg)	Freight by ship (kg.km)
Ë	Quantity	9.27E-02	3.89E+00	1.13E+01	4.00E+01	1.60E-02	1.32E-02	6.27E-02	4.75E+02
umption	Note								
	Classification	Material	Material	Energy	Energy	Energy	Material		
Cons	Distribution	Raw wood (Imported) (kg)	Low density polyethylene (kg)	LPG(NPG) as fuel (kg)	Diesel truck: 20 ton (kg.km)	Incineration: Industrial waste (kg)	PP (kg)		
	Quantity	1.00E-02	1.17E-03	1.25E-02	1.80E+01	1.06E-01	2.38E-03		
	Note								
a inge	Classification								
Dischi	Distribution								
/wols	Quantity								
SII.	Note	_							_

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)			
	Conditions			Loading Ratio (%w)			Distance (km)	Loading Ratio (%w)	
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (kill)	Loading Ratio (%W)	Load (kg·km)
E	Quantity	1.25E+01	5.00E+01	3.52E+01	1.77E+03	1.25E+01	3.30E+03	1.00E+02	4.12E+04
ibuti	Note								
	Means of transportation	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:				
Distr	means or transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)				
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	1.25E+01	1.00E+02	3.52E+01	3.55E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Diesel truck:	Freight by	Diesel truck:	Diesel truck:	Cold-Rolled	Electroplated	Stainless	Aluminum
	Distribution	20 ton (kg.km)	ship (kg.km)	2 ton (kg.km)	10 ton (kg.km)	steel plate (kg)	steel Plate (kg)	steel plate (kg)	plate (kg)
	Quantity	3.87E+04	6.58E+05	1.77E+03	8.44E+04	3.35E+00	3.16E+01	9.18E-01	1.51E+00
	Note	Distribution of consumables used in 5 years							
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Glass (kg)	High density polyethylene (kg)	Low density polyethylene (kg)	PP (kg)	PS (kg)	PBT (kg)	Polycarbonate (kg)	PC-ABS (70/30) (kg)
	Quantity	1.28E-01	3.07E-02	3.74E+00	4.00E+00	3.26E+01	3.85E-02	2.95E+00	4.56E-01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	POM (polyacetal) (kg)	ABS (kg)	AS resin (kg)	MMA resin (kg)	PET (kg)	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber(NBR) (kg)	Corrugated cardboard (kg)
F	Quantity	3.33E+00	2.58E+00	2.02E+01	1.24E-02	3.06E+00	7.33E-01	9.27E+00	6.64E+01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Paper (Western style) (kg)	Assembled circuit board (kg)	Medium-sized motor (kg)	Press molding: Iron (kg)	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Glass molding (kg)	Parts assembly (kg)
	Quantity	8.65E-01	3.87E-01	3.28E-01	3.28E+01	1.51E+00	6.20E+01	1.28E-01	2.76E+01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Process	
	Distribution	Electricity (kWh)	Heavy oil as fuel (kg)	Diesel oil as fuel (kg)	LPG(NPG) as fuel (kg)	LNG as fuel(kg)	Electricity (kWh)	Incineration: Industrial waste (kg)	
	Quantity	5.65E+02	1.41E+01	1.68E-01	1.60E-01	4.48E-01	2.61E+02	4.66E+00	
	Note	Electricity consumption for 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Packaging materials for distribution of ingredient	

Note: At "Use Stage", the product electricity consumption in 5 years usage period is 565 kWh .

4.2 Disposition/Recycle information on consumables and replacement parts

S	Classification	Consumption	Process	Process	Process		
nable	Distribution	Diesel truck: 4 ton (kg·km)	Shredding (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)		
l ms	Quantity	8.80E+03	9.10E+01	1.23E+02	3.88E+01		
S	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected		

ote

5. Disposition/Recycle stage information (per product): process method and scenarios

	Classification	Consumption	Process	Process	Process		
.0	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:		
Jari		4 ton (kg.km)		landfill (as ash) (kg)	General waste (kg)		
Se	Quantity	1.08E+03	9.23E+00	7.64E+00	3.56E+00		
S	Note	Machines not	Machines not	Machines not	Machines not		
	Note	collected	collected	collected	collected		

Note