Product Environmental Aspects Declaration

EP and IJ printer (PCR-ID:AD-04)



No. AD-16-E758 Date of publication 06/10/2016



Contact us KYOCERA Document Solutions Inc. **CSR Division**

Product Environmental Planning Dep.

TEL: +81-6-6764-3760 FAX: +81-6-6764-3780



http://www.kyoceradocumentsolutions.co.jp/ **ECOSYS P7040cdn**

Making Technology: Electrophotographic Printer (EP) Printng Speed: Monoclome 40 Pages per minute in A4 Color 40 Pages per minute in A4


Maximum priting paper: A4 **Duplex function: Standard**

The Environmental load for life-cycle

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO ₂ equivalent)	846.1kg (749.6kg)
Acidification (SO ₂ equivalent)	1.2kg (1.1kg)
Energy resources (crude oil equivalent)	18,990MJ (16,399MJ)

Figures in () indicated environmental impact including recycle effect *note3

Warming load CO₂ equivalent of each stage[kg]



Use stage: Printing Mono 480,000/Col 480,000 A4 sheets in 5 years.

The environmental load of sheet in"Use" stage is not included in above data

Notes

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR; Product Specification Criteria. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- 3. Recycle Effect illustrates an indirect influence to other products/services.
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 5. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.


[Supplemental environmental information]

- Conformed to the International ENERGY STAR® Program.
- Manufactured at ISO14001 certified factories.
- Plastic housing and outer package: halogenated flame retardants are not used.

PCR review was conducted by: PCR Deliberation Committee, January 01,2008, Name of reprentative: Youji Uchiyama, Independent verification of the declaration and data, according to ISO14025:2006 ☐internal ■external Third party verifier: < name of the third party verifier *> Hiroo Sakazaki Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written. The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

Product Environmental Information Data Sheet (PEIDS)





PCR name	EP and IJ printer		Product type	ECOSYS P7040cdn			
PCR code	AD-04	Product weight (kg)	34.2	Package (kg)	7.14	Weight total (kg)	41.34

	_			Life Cycle Stage	I Inda	Produ	uction	Distribution	Use	Discosition	Recycle
In/Ou	ut item	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Effect
		Е,	oray C	Consumption	MJ	5.06E+03	5.99E+02	8.53E+01	1.32E+04	3.47E+01	-2.59E+03
			lergy C	onsumption	Mcal	1.21E+03	1.43E+02	2.04E+01	3.16E+03	8.28E+00	-6.19E+02
			ses	Coal	kg	3.06E+01	3.85E+00	1.99E-04	5.72E+01	4.08E-02	-8.42E+00
			isoni	Crude oil (for fuel)	kg	5.37E+01	4.61E+00	1.86E+00	9.72E+01	6.47E-01	-2.09E+01
			9	LNG	kg	1.08E+01	1.93E+00	2.88E-02	3.38E+01	2.97E-02	-1.76E+00
			Ener	Uranium content of an ore	kg	1.16E-03	2.61E-04	1.35E-08	3.46E-03	2.76E-06	-5.88E-05
	_			Crude oil (for material)	kg	1.46E+01	0	0	4.57E+01	0	-2.81E+01
	tio	(0		Iron content of an ore	kg	1.39E+01	0	0	5.51E+00	0	-7.12E+00
	μ	Se		Cu content of an ore	kg	9.83E-01	0	0	4.52E-02	0	-7.35E-01
	sul	resources		Al content of an ore	kg	1.03E+00	0	0	6.08E-01	0	-5.99E-01
	ou	SSC	S	Ni content of an ore	kg	3.80E-02	0	0	2.99E-02	0	-2.72E-02
	O	2	resources	C content of an ore	kg	5.57E-02	0	0	4.24E-02	0	-3.93E-02
	eo.	ple	ă	Mn content of an ore	kg	7.09E-02	0	0	3.40E-02	0	-1.00E-02
	ınc	sti	380	Pb content of an ore	kg	5.45E-02	0	0	3.67E-03	0	-5.98E-02
	esc	an		Sn content of an ore	kg	0	0	0	0	0	0
	Impact by Resource Consumption	Exhaustible	Mineral	Zn content of an ore	kg	5.37E-01	0	0	3.61E-02	0	-5.87E-01
	by	ш	ii.	Au content of an ore	kg	0	0	0	0	0	0
	ct		Σ	Ag content of an ore	kg	0	0	0	0	0	0
က္ဆ	pa			Silica Sand	kg	1.32E+00	0	0	1.68E-01	0	-3.39E-01
anaiyses	<u>u</u>			Halite	kg	6.46E+00	0	0	1.03E+00	9.57E-05	-2.29E+00
aj				Limestone	kg	3.71E+00	0	0	1.21E+00	6.20E-03	-1.24E+00
an				Natural soda ash	kg	1.11E-01	0	0	1.02E-02	0	-9.82E-03
			Wood	kg	1.47E+01	0	0	1.17E+01	0	-1.24E+01	
nventory		1	Water	kg	2.98E+04	3.10E+03	1.51E-01	4.23E+04	3.10E+01	-2.77E+03	
ķ	υţ			ICO2	kg	2.78E+02	3.08E+01	6.06E+00	5.10E+02	2.40E+00	-9.27E+01
ے	me		4	Sox	kg	2.00E-01	2.32E-02	3.15E-03	3.66E-01	2.70E-03	-6.56E-02
	oni		ere	Nox	kg	3.50E-01	2.00E-02	1.95E-02	5.15E-01	3.02E-02	-1.69E-01
	Σį		Š	N2O	kg	2.36E-02	5.02E-04	1.15E-03	4.24E-02	3.86E-05	-1.39E-02
	e		lso	CH4	kg	3.08E-03	3.44E-03	3.61E-08	9.24E-03	7.38E-06	-1.45E-04
	the		Atmosphere	CO	kg	3.92E-02	4.49E-03	3.26E-03	9.86E-02	1.16E-02	-1.28E-02
	to		⋖	NMVOC	kg	6.01E-03	1.36E-03	7.07E-08	1.81E-02	1.45E-05	-2.85E-04
	ge		\$	CxHy	kg	1.11E-02	1.60E-04	7.20E-04	1.30E-02	6.02E-04	-6.67E-03
	har			Dust	kg	3.57E-02	1.21E-03	2.08E-03	3.89E-02	2.39E-03	-2.03E-02
	isc	E	·Ē	BOD	kg	-	2.42E-03	-	-	-	-
	Q/c	yste	domain	COD	kg	-	-	-	-	-	-
	impact by Emission/Discharge to the environment	to Water system	er d	N total	kg	-	-	-	-	-	-
	iss	Nat	Water	P total	kg	-	-	-	-	-	-
	Επ	to /	0	SS	kg	-	-	-	-	-	-
	by		me	Unspecified Solid Waste	kg	2.34E+00	6.85E-03	0	1.75E+01	3.13E-06	-1.66E+00
	ct		system	Slag	kg	5.49E+00	0	0	1.80E+00	0	-2.84E+00
	ра		Soils	Sludge	kg	1.91E+00	0	0	1.30E+00	0	-1.29E+00
	Ιπ		\$	Low level radio-active waste	kg	8.09E-04	1.82E-04	9.43E-09	2.41E-03	1.93E-06	-4.11E-05
ınt	by Res			Energy resources (crude oil equivalent)	kg	9.58E+01	1.15E+01	1.90E+00	2.03E+02	7.31E-01	-2.89E+01
assessment	b Re		Committee	Mineral resources (Iron ore equivalent)	kg	2.93E+02	0	0	6.98E+01	0	-2.65E+02
sse).comics		ere	Global Warming (CO2 equivalent)	kg	2.85E+02	3.10E+01	6.37E+00	5.21E+02	2.41E+00	-9.65E+01
1886	toente		hds	Acidification (SO2 equivalent)	kg	4.44E-01	3.72E-02	1.68E-02	7.26E-01	2.38E-02	-1.84E-01
ت ت	Sichogo		\tmc	Ozone Depletion (CFC-11 equivalent)	kg	0	0	0	0	0	0
Impact	B) wash		\$	Photochemical Oxidant	kg	2.15E-02	1.15E-03	1.14E-03	2.87E-02	1.23E-03	-1.11E-02
	8			Eutrophication (Phosphate equivalent)	ka	0	0	0	0	0	0

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts)
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts. Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere. Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "O" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
 - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- 1. We include package and attached articles, such as CD-ROM, operation manual in the product weight. Toner container as standard is included in the use stage, not in the product weight.
- 2. Production stage: Environmental impacts on main product, toner supplied with and drum are included in this stage. Production of main product is included as China production. Toner and drum are included as Japan production.
- 3.Transportation stage: Marine transport distance of a main product is 2.600km and domestic transport distance based on PCR provisions is 100km.
- 4.Use stage: Based on PCR provision, impact on 480,000 sheets monochrome printing and 480,000 sheets color printing by user for five years is considered. 5.Disposal/Recycle: We have calculated on the basis of a performance-based recycle scenario.
- This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Product data sheet

(Input data and parameters for LCA

	(Input data and parameters for LCA)
Document control no.	F-03s-03
Product vendor	KYOCERA Document Solutions Inc.
EcoLEaf registration no.	AD-16-E758



PCR name	EP & IP Printer (PCR-ID:AD-04)	Product type	ECOSYS P7040dn				
LCA/LCIA in units of:	1 Unit	Product weight (kg)	34.2	Package (kg)	7.14	Weight total (kg)	41.34

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bre	eakdown of p	rimary materials		Math breakdown of parts, which	ch need to apply	Processing / Assembly Base U	nits (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Carbon steel(kg)	1.17E+01	Paper (kg)	6.90E+00	Press molding:Iron (kg)	1.19E+01	Parts assembly (kg)	4.10E+01
	SUS (kg)	2.39E-01	Assembled circuit board (kg)	3.47E+00	Press molding:Nonferrous metal (kg)	1.12E+00		
+	Cu (kg)	6.38E-01	Medium-sized motor (kg)	1.57E+00	Injection molding (kg)	1.56E+01		
roduct	Al (kg)	8.42E-01			Blow molding (kg)	6.99E-02		
	Glass (kg)	2.92E-01			Glass molding (kg)	2.92E-01		
	Thermoplastics resin (kg)	1.56E+01						
	thermosetting resin (kg)	7.05E-02						
	Rrubber (kg)	3.36E-02						
	Subtotal	2.94E+01	Subtotal	1.19E+01				
		Total		4.13E+01	Subtotal	2.90E+01	Subtotal	4.10E+01

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

 ${\rm SOx}$ and ${\rm NOx}$ should be indicated in ${\rm SO_2},\,{\rm NO_2}$ equivalent.

≃	Classification	Energy	Material	Energy	Energy			
듈	Distribution	Electricity (kWh)	Industrial water (kg)	Heavy oil as fuel (kg)	Gasoline as fuel (kg)			
insuo	Quantity	2.94E+01	1.82E+02	2.60E-01	2.99E-03			
ទី	Note							
arge	Classification	Water system	Atmosphere					
Disch	Distribution	BOD	CH4					
/wis	Quantity	2.42E-03	2.74E-03					
Emis	Note	•					·	

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

o	Means of transportation	Diesel truck:10 ton (kg·km)	Freight by ship (kg·km)						
E E	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
Ξ	Quantity	4.13E+01	1.00E+02	6.95E+01	5.95E+03	4.13E+01	2.60E+03	1.00E+02	1.07E+05
Dis	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Process	Process	Process	Process	Process	Process
	Distribution	Electricity (kWh)	Industrial water (kg)	Injection molding (kg)	Blow molding (kg)	Parts assembly (kg)	Diesel truck:2 ton (kg·km)	Press molding:Iron (kg)	Press molding:Nonferrous metal (kg)
	Quantity	8.39E+02	1.55E+02	2.53E+01	9.17E-02	3.54E+01	2.50E+04	3.68E+00	5.22E-01
	Note								
	Classification	Process	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
duct	Distribution	Glass molding (kg)	Carbon steel(kg)	SUS (kg)	Cu (kg)	Al (kg)	Glass(kg)	Thermoplastics resin (kg)	thermosetting resin (kg)
Prod	Quantity	4.91E-02	5.26E+00	1.89E-01	3.69E-02	5.75E-01	4.91E-02	5.66E+01	9.17E-02
	Note								
	Classification	Consumption	Consumption	Consumption					
	Distribution	Rrubber (kg)	Paper (kg)	Assembled circuit board (kg)					
	Quantity	4.42E-02	5.40E+00	2.47E-01					
	Note								

Note

4.2 Disposition/Recycle information on consumables and replacement parts

	Classification	Process	Process	Process	Process	Process	Process	Process	Deduction
	Distribution	Recycle:to copper plate (kg)	Recycle:to Aluminum plate (kg)	Recycle:to Thermoplastic pellet (kg)	Recycle:to corrugated cardboard (kg)	Recycle:to Glass (kg)	Shredding (kg)	Recycle:to cold-rolled steel (kg)	Carbon steel(kg)
sel	Quantity	1.66E-01	2.30E-01	2.33E+01	3.06E+00	1.97E-02	3.71E+01	2.21E+00	2.13E+00
nab	Note								
II SI	Classification	Deduction	Deduction	Deduction	Deduction	Deduction			
S	Distribution	SUS (kg)	Cu (kg)	Al (kg)	Thermoplastics resin (kg)	Paper (kg)			
	Quantity	7.54E-02	1.66E-01	2.30E-01	2.33E+01	3.06E+00	•		
	Note								

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

. Dispu	JSILIUII/NEC	ycle stage illion	nation (per prodi	uct). process me	emou and Scenar	103			
	Classification	Process	Process	Process	Process	Process	Process	Process	Process
	Distribution	Diesel truck:10 ton (kg·km)	Diesel truck:2 ton (kg·km)	Electricity (kWh)	Incineration: Industrial waste (kg)	Shredding (kg)	Recycle:to cold-rolled steel (kg)	Recycle:to copper plate (kg)	Recycle:to Aluminum plate (kg)
	Quantity	2.38E+03	1.04E+04	7.40E-01	9.57E-02	4.13E+01	4.78E+00	2.27E+00	3.37E-01
	Note								
	Classification	Process	Process	Process	Deduction	Deduction	Deduction	Deduction	Deduction
Scenario	Distribution	Recycle:to Thermoplastic pellet (kg)	Recycle:to corrugated cardboard (kg)	Recycle:to Glass (kg)	Carbon steel(kg)	SUS (kg)	Cu (kg)	Al (kg)	Glass (kg)
cer	Quantity	6.23E+00	2.76E+00	1.17E-01	4.68E+00	9.57E-02	2.27E+00	3.37E-01	1.17E-01
S	Note								
	Classification	Deduction	Deduction						
	Distribution	Thermoplastics resin (kg)	Paper (kg)						
	Quantity	6.23E+00	2.76E+00						
	Note								

Note

6. Others

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

The following list is a list of the basic units which we use to implement LCA.

These basic units refer to the Eco Leaf Environmental Label LCI Common Basic Unit(V2.1) which is published on the following URL. (URL:http://www.ecoleaf-jemai.jp/application/data/basicunit_en20150601.pdf).

No Field Base Unit Name 1 Material Production (Metal) Cold-Rolled steel plate 2 Electroplated steel Plate	Unit
· · · · · · · · · · · · · · · · · · ·	1.0
2 Electropiated steel Plate	kg
3 Hot Dipped steel plate	kg
The second secon	kg
6 Stainless Steel Plate	kg
7 Copper plate	kg
8 Aluminum plate	kg
16 Material Production Glass	kg
26 Material Production High density polyethylene	kg
Low density polyethylene	kg
28 Polypropylene	kg
29 Polystyrene	kg
PBT PBT	kg
Polycarbonate	kg
Polycarbonate-ABS (70/30)	kg
POM (Polyacetal)	kg
PVDC	kg
ABS ABS	kg
38 MMA Resin	kg
PA66 (Polyamide 66)	kg
PET PET	kg
42 Expandable hard polyurethane (Har	d) kg
48 Material Production Nitrile-butadiene rubber (NBR)	kg
50 Natural rubber	kg
67 Material Production Corrugated cardboard	kg
69 Paper (Western style)	kg
76 Parts Production Assembled circuit board	kg
78 Medium-sized motor	kg
85 Processing Press molding: Iron	kg
86 Press molding: Nonferrous metal	kg
87 Injection molding	kg
88 Blow molding	kg
89 Glass molding	kg
90 Assembly Parts assembly	kg
91 Transportation Diesel truck: 2 ton	kg.k m
93 Diesel truck: 10 ton	kg.k m
97 Freight by ship	kg.k m
99 Electric Power and Fuel Electricity	kWh
100 Heavy oil as fuel	kg
119 LNG	kg
125 Utility (Water) Industrial water	kg
129 Disposal and Recycling Shredding	kg
133 Disposal and Recycling Incineration to landfill (as ash)	kg
134 Incineration: Industrial waste	kg
136 Landfill: General waste	kg
138 Disposal and Recycling Recycle: to cold-rolled steel	kg
	kg
Recycle: to copper plate	1
139 Recycle: to copper plate 140 Recycle: to Aluminum plate	kg
	kg kg
Recycle: to Aluminum plate	