# Product Environmental Aspects Declaration

EP and IJ printer (PCR-ID:AD-04)



No. AD-16-E760 Date of publication June/24/2016

## **TOSHIBA**

Leading Innovation >>>

TOSHIBA TEC CORPORATION
Corporate Quality & Environmental Group
TEL: +81-3-6830-9100

URL http://www.toshibatec.co.jp

# A8005 OIGUTE:

- Marking tecnologies : Electrophotographic Printer(EP)
- ■Color: Monochrome(B/W)
- Printing Speed: 50 LTR Pages per minutes
- Maximum Paper Size : LD Duplex copying : Standard


The number of copies when used for 5 years is 1,500,000



Document Feeder and Large Capacity Feeder are optional units. They are not included in the calculation.

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO2 equivalent)	1403kg (1199kg)
	2.0kg
Acidification (SO2 equivalent)	(1.7kg)
Energy resources (crude oil equivalent)	26,679MJ
Energy resources (crade on equivalent)	(23,253MJ)

% Figures in ( ) indicated environmental impact including recycle effect \*note3



#### Notes

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at <a href="http://www.ecoleaf\_jemai.jp/eng/">http://www.ecoleaf\_jemai.jp/eng/</a> for details.
- 3. Recycle Effect illustrates an indirect influence to other products/services.
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 5. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

#### [Supplemental environmental information]

- •Certified to the international ENERGY STAR Program V2.0, EU RoHS
- ·Manufactured at ISO14001 certified factories

PCR review was conducted by : PCR Deliberation Committee, January 01,2008, Name of representative: Youji Uchivama, University of Tsukuba, Graduate School


Independent verification of the declaration and data, according to ISO14025:2006 □internal ■external Third party verifier: Yasuo Koseki

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

The Ecoleaf is an environmental labeling program that belongs to the ISO-Type III category.

<sup>\*</sup> In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

### Product Environmental Information Data Sheet (PEIDS)





PCR name	EP and IJ print	er	Product type	TOSHIBA MFP e-STUDIO5008A			
PCR code	AD-04	Product weight (kg)	57.0	Package (kg)	7.3	Weight total (kg)	64.3

		_		Life Cycle Stage	11.2	Produ	uction	D: 47		B: 32	Recycle
In/O	ut iten	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Effect
	Energy Consumption			Concumption	MJ	5.50E+03	6.33E+02	7.02E+02	1.98E+04	3.88E+01	-3.43E+03
			lergy C	consumption	Mcal	1.31E+03	1.51E+02	1.68E+02	4.73E+03	9.26E+00	-8.18E+02
			seo	Coal	kg	4.36E+01	4.54E+00	1.64E-03	8.47E+01	1.35E-01	-4.28E+01
			in ose	Crude oil (for fuel)	kg	5.29E+01	5.23E+00	1.53E+01	1.98E+02	5.94E-01	-2.63E+01
			rgy re	LNG	kg	1.01E+01	2.27E+00	2.37E-01	4.54E+01	7.50E-02	-2.49E+00
			Ene	Uranium content of an ore	kg	1.07E-03	3.07E-04	1.11E-07	4.72E-03	9.17E-06	-1.35E-04
	L C			Crude oil (for material)	kg	1.81E+01	0	0	3.21E+01	0	-1.63E+01
	otic	Ø		Iron content of an ore	kg	2.94E+01	0	0	1.14E+01	0	-3.93E+01
	Consumption	ce		Cu content of an ore	kg	1.12E+00	0	0	0	0	-4.45E-01
	ารเ	Ino		Al content of an ore	kg	3.09E-01	0	0	8.86E-01	0	-1.07E+00
	Š	es	S	Ni content of an ore	kg	6.79E-01	0	0	7.58E-01	0	-1.44E+00
		e	õ	C content of an ore	kg	9.29E-01	0	0	1.03E+00	0	-1.96E+00
	ırc	qi	00	Mn content of an ore	kg	2.57E-01	0	0	1.83E-01	0	-2.30E-01
	301	nst	Ge	Pb content of an ore	kg	6.86E-02	0	0	0	0	-3.62E-02
	by Resource	Exhaustible resources	Exhaustible res	Sn content of an ore	kg	0	0	0	0	0	0
	γF	E	je	Zn content of an ore	kg	6.75E-01	0	0	0	0	-3.55E-01
	t b		⋚	Au content of an ore	kg	0	0	0	0	0	0
	mpact		_	Ag content of an ore	kg	0 2.60E+00	0	0	0 1.26E-01	0	0 -1.56E+00
ses	μ			Silica Sand	kg		1.91E-07	0		9.11E-03	-6.41E+00
anaiyses	_			Halite Limestone	kg kg	1.01E+01 7.09E+00	0	0	3.61E+00 3.63E+00	5.89E-01	-0.41E+00 -7.25E+00
E L				Natural soda ash		2.30E-01	0	0	0	0	-1.42E-01
\ \S				Wood	kg kg	1.38E+01	0	0	3.98E+01	0	-5.36E+01
ğ			-	Water	ka	2.55E+04	3.44E+03	1.24E+00	6.99E+04	1.12E+02	-6.40E+03
nventory				CO2		3.08E+02	3.56E+01	4.98E+01	9.51E+02	1.58E+01	-0.40E+03
_≥	ien	to Atmosphere		Sox	kg ka	2.03E-01	2.69E-02	3.12E-02	5.58E-01	9.06E-03	-1.55E-01
	nu			Nox	kg	3.63E-01	2.16E-02	2.53E-01	1.00E+00	3.51E-02	-2.72E-01
	/iro		e Pe	N2O	kg	2.53E-02	5.09E-04	8.14E-03	1.27E-01	6.94E-05	-1.73E-02
	en		dsc	CH4	kg	2.86E-03	8.20E-04	2.97E-07	1.26E-02	2.45E-05	-3.28E-04
	þe		Ĕ	CO	kg	4.39E-02	5.23E-03	6.89E-02	2.02E-01	8.48E-03	-3.98E-02
	o t		₹	NMVOC	kg	5.59E-03	1.61E-03	5.82E-07	2.47E-02	4.81E-05	-6.41E-04
	Je t		\$	CxHy	kg	1.23E-02	1.06E-04	7.36E-03	3.26E-02	3.58E-04	-8.69E-03
	arç			Dust	kg	4.17E-02	1.16E-03	2.38E-02	7.14E-02	1.36E-03	-3.46E-02
	Emission/Discharge to the environment	Ε	.⊑	BOD	kg	-	-	-	-	-	-
	į	to Water system	o Water domain	COD	kg	-	-	-	-	-	-
	ion	er s.	- o	N total	kg	-	-	-	-	-	-
	iss	Nati	Vate	P total	kg	-	-	-	-	-	-
	E	to	to	SS	kg	-	-	-	-	-	-
	by E		E	Unspecified Solid Waste	kg	2.09E+00	1.24E-06	0	1.55E+00	8.53E-01	-9.63E-01
	t		system	Slag	kg	1.11E+01	0	0	3.96E+00	0	-1.32E+01
	Impact		Soil	Sludge	kg	3.97E-01	0	0	1.90E+00	0	-2.30E+00
	lπ		5	Low level radio-active waste	kg	7.52E-04	2.15E-04	7.77E-08	3.29E-03	6.41E-06	-9.45E-05
it	by Res		and the second	Energy resources (crude oil equivalent)	kg	1.02E+02	1.34E+01	1.56E+01	3.46E+02	8.46E-01	-5.79E+01
эщ	م چ		Description	Mineral resources (Iron ore equivalent)	kg	8.64E+02	0	0	6.30E+02	0	-1.32E+03
ess	rormeré		nere	Global Warming (CO2 equivalent)	kg	3.14E+02	3.57E+01	5.20E+01	9.86E+02	1.58E+01	-2.05E+02
ass	pe to envi		ydso	Acidification (SO2 equivalent)	kg	4.57E-01	4.20E-02	2.08E-01	1.26E+00	3.36E-02	-3.45E-01
ct	Discharg		Atm	-	-	-	-	-	-	-	-
Impact assessment	mission/		\$	-	-	-	-	-	-	-	-
드	by E		-	-	-	-	-	-	-	-	-

#### [Notes for readers: EcoLeaf common rules]

#### I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. Disposition/Recycle' stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production
- E. 'Recycle Effect' illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.

  Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.

  Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

#### II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

#### III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO 2 in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

#### IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

#### [Notes for readers: Target product specific]

#### **Product data sheet**

	(Input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	TOSHIBA TEC CORPORATION
EcoLEaf registration no.	AD-16-E760



PCR name	EP and IJ printer(PCR-ID:AD-04)	Product type	TOSHIBA MFP e-STUDIO5008A				
LCA/LCIA in units of:	1	Product weight (kg)	57.0	Package (kg)	7.3	Weight total (kg)	64.3

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bre	eakdown of p	rimary materials		Math breakdown of parts, wh	ich need to apply	Processing / Assembly Base Ur	nits (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Ordinary steel	2.55E+01	Paper	6.50E+00	Press molding:Iron (kg)	3.12E+01	Parts assembly (kg)	1.08E+00
	Stainless steel	4.29E+00	Semiconductor substrate	4.31E+00	Press molding:Nonferrous metal (kg)	7.18E+00		
	Other metals	1.48E+00			Injection molding (kg)	2.59E+01		
- Inct	Aluminum	1.75E-01						
rodi	Glass	1.88E+00						
<u> </u>	Thermoplastic resin	1.97E+01						
	Thermosetting resin	2.38E-01						
	Rubber	1.49E-01						
	Subtotal	5.35E+01	Subtotal	1.08E+01				
		Total		6.43E+01	Subtotal	6.43E+01	Subtotal	1.08E+00

#### 2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

ion	Classification	Energy	Energy	Energy	Material		
umption	Distribution	Electricity (kWh)	Heavy oil as fuel (kg)	Furnace LPG (kg)	Industrial water (kg)		
S	Quantity	4.53E+00	1.00E-02	9.00E-02	3.30E-02		
ō	Note						
arge	Classification	Water system					
Disch	Distribution	Sewage processing (kg)					
/uois	Quantity	3.30E-02					
Emis	Note						
Note							

Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/

					,,					
ı	ion	Means of transportation	Freight by ship (kg·km)	Diesel truck:10 ton (kg·km)	Diesel tdischarges.	Diesel truck:10 ton (kg·km)	Diesel truck:10 ton (kg·km)			
-	₹	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
-	strib	Quantity	6.43E+01	1.17E+04	1.00E+02	7.50E+05	6.43E+01	1.00E+03	4.63E+01	1.39E+05
- 1	ä	Note								

Note The main body products are transported from China to USA.

#### 4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this

-	Classification  Distribution	Consumption Cold-Rolled	Consumanalys	is Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
I	Distribution	Cold-Rolled			Concumption	Consumption	Consumption	Consumption	Consumption
		steel plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)	Low density polyethylene (kg)	Polystyrene (kg)	Polycarbonate (kg)	POM (polyacetal) (kg)	PET (kg)
	Quantity	9.50E+00	4.79E+00	8.38E-01	1.30E-01	1.40E+01	2.70E-03	4.46E-01	2.45E+01
	Note								
(	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Process	Consumption
ı	Distribution	Expandable hard polyurethane (Hard) (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Blow molding (kg)	Freight by ship (kg·km)	Electricity (kWh)
	Quantity	2.55E+00	1.86E+01	6.90E-02	2.22E+01	1.53E+01	1.30E-01	3.24E+05	1.16E+03
Product	Note								
Pro	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Discharge
	Distribution	Heavy oil as fuel (kg)	Gasoline as fuel (kg)	Furnace urban gas (13A) (m3)	Furnace LPG (kg)	Urban gas (13A) (m3)	Industrial water (kg)	Clean water (kg)	Sewage processing (kg)
	Quantity	2.00E-03	5.00E-02	3.09E+00	6.56E+01	2.37E+00	4.66E+00	8.90E+02	2.11E+02
	Note								
(	Classification	Process							
ı	Distribution	Diesel truck: 4 ton (kg·km)							
	Quantity	1.27E+05							
	Note								

#### 4.2 Disposition/Recycle information on consumables and replacement

7.2	Diapositio	il/Recycle illion	nation on const	imables and rep	acement				
	Classification	Process	Process	Process	Process	Process	Process	Process	Process
		Landfill:	Incineration:		<b>Pærés</b> cle:	Recycle:	Recycle:	Recycle:	Recycle:
	Distribution	Industrial waste	Industrial waste	Shredding (kg)	to cold-rolled	to Aluminum	to Thermoplastic	to corrugated	to Paper
		(kg)	(kg)		steel (kg)	plate (kg)	pellet (kg)	cardboard (kg)	(kg)
es	Quantity	5.70E-01	7.76E+00	1.83E+01	1.43E+01	8.40E-01	8.81E+00	1.86E+01	7.00E-02
ısumables	Note								
	Classification	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	
Consi	Distribution	Cold-Rolled steel plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)	Polystyrene (kg)	Expandable hard polyurethane (Hard) (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	
	Quantity	9.50E+00	4.79E+00	8.40E-01	7.20E+00	1.31E+00	1.86E+01	7.00E-02	
	Note								

5. Disposition/Recycle stage information (per product): process method and scenarios

	Classification	Process	Process	Process	Process	Process	Process	Process	Process
	Distribution	Shredding (kg)	Landfill: Industrial waste (kg)	Incineration: Industrial waste (kg)	Diesel truck: 10 ton (kg·km)	Recycle: to cold-rolled steel	Recycle: to copper plate (kg)	Recycle: to Aluminum plate (kg)	Recycle: to Glass (kg)
	Quantity	4.02E+01	8.53E-01	9.09E+00	1.39E+04	3.13E+01	1.48E+00	1.75E-01	1.69E+00
	Note								
	Classification	Process	Process	Process	Deduction	Deduction	Deduction	Deduction	Deduction
Scenario	Distribution	Recycle: to Thermoplastic pellet (kg)	Recycle: to corrugated cardboard (kg)	Recycle: to Paper (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Copper plate (kg)	Aluminum plate (kg)	Glass (kg)
တ	Quantity	1.32E+01	6.45E+00	5.10E-02	2.55E+01	4.29E+00	1.48E+00	1.75E-01	1.69E+00
	Note								
	Classification	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	
	Distribution	Polystyrene (kg)	Polycarbonate (kg)	Polycarbonate- ABS (70/30) (kg)	ABS (kg)	PET (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	
	Quantity	2.28E+00	1.29E+00	2.36E+00	2.81E+00	6.54E-01	6.45E+00	5.10E-02	
	Note								

Others

6. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.