製品環境情報

Product Environmental Aspects Declaration

EP and IJ printer (PCR-ID:AD-04)



No. AD-16-E763 Date of publication June/24/2016

TOSHIBA

Leading Innovation >>>

TOSHIBA TEC CORPORATION
Corporate Quality & Environmental Group
TEL: +81-3-6830-9100

URL http://www.toshibatec.co.jp

A8006 OIGUTS:

- Marking tecnologies : Electrophotographic Printer(EP)
- ■Color: Monochrome(B/W)
- Printing Speed: 30 LTR Pages per minutes (B/W)
- Maximum Paper Size: LD Duplex copying: Standard


The number of copies when used for 5 years is 540,000



Document Feeder and Large Capacity Feeder are optional units. They are not included in the calculation.

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO2 equivalent)	853kg
Global Warlining (CO2 equivalent)	(708kg)
Acidification (SO2 equivalent)	1.3kg
Acidification (SO2 equivalent)	(1.0kg)
Energy resources (crude oil equivalent)	15,553MJ
Energy resources (crude on equivalent)	(13,154MJ)

% Figures in () indicated environmental impact including recycle effect *note3



Notes

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf_jemai.jp/eng/ for details.
- $3. \ \ Recycle\ Effect\ illustrates\ an\ indirect\ influence\ to\ other\ products/services.$
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 5. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

- •Certified to the international ENERGY STAR Program V2.0, EU RoHS
- ·Manufactured at ISO14001 certified factories

PCR review was conducted by : PCR Deliberation Committee, January 01,2008, Name of representative: Youji Uchivama, University of Tsukuba, Graduate School


Independent verification of the declaration and data, according to ISO14025:2006 □internal ■external Third party verifier: Yasuo Koseki

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

The Ecoleaf is an environmental labeling program that belongs to the ISO-Type III category.

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)





製品環境情報

PCR name	EP and IJ printer		Product type	TOSHIBA MFP e-STUDIO3008A			
PCR code	AD-04	Product weight (kg)	54.9	Package (kg)	7.3	Weight total (kg)	62.2

	_			Life Cycle Stage	11.3	Prod	uction	District of a	11	B1	Recycle
In/O	ut iten	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Effect
					MJ	5.33E+03	6.14E+02	6.85E+02	8.88E+03	3.79E+01	-2.40E+03
		Er	nergy C	Consumption	Mcal	1.27E+03	1.47E+02	1.64E+02	2.12E+03	9.05E+00	-5.73E+02
			88	Coal	kg	4.22E+01	4.40E+00	1.60E-03	3.80E+01	1.30E-01	-3.25E+01
			ss our	Crude oil (for fuel)	kg	5.13E+01	5.07E+00	1.50E+01	8.98E+01	5.84E-01	-1.74E+01
			argy re	LNG	ka	9.73E+00	2.20E+00	2.31E-01	2.05E+01	7.24E-02	-1.52E+00
			E	Uranium content of an ore	kg	1.05E-03	2.98E-04	1.08E-07	2.16E-03	8.83E-06	-8.56E-05
	ے			Crude oil (for material)	kg	1.75E+01	0	0	1.20E+01	0	-1.10E+01
	l ig	(n		Iron content of an ore	kg	2.88E+01	0	0	5.09E+00	0	-3.27E+01
	ш	čě		Cu content of an ore	kg	1.06E+00	0	0	0	0	-4.42E-01
	ns	ğ		Al content of an ore	kg	2.82E-01	0	0	4.04E-01	0	-5.85E-01
	by Resource Consumption	SSC	တ္	Ni content of an ore	kg	5.58E-01	0	0	2.05E-01	0	-7.64E-01
	O	E E	Ö	C content of an ore	kg	7.66E-01	0	0	2.79E-01	0	-1.05E+00
	5	Exhaustible resources	В	Mn content of an ore	kg	2.36E-01	0	0	6.00E-02	0	-1.31E-01
	no		eSi	Pb content of an ore	kg	6.79E-02	0	0	0	0	-3.59E-02
	esc	Jac	Wineral resources	Sn content of an ore	kg	0	0	0	0	0	0
	æ	×	6.0	Zn content of an ore	kg	6.68E-01	0	0	0	0	-3.53E-01
	Q	ш	. <u>≧</u>	Au content of an ore	kg	0	0	0	0	0	0
	3C		2	Ag content of an ore	kg	0	0	0	0	0	0
S	Impact k			Silica Sand	kg	2.57E+00	0	0	5.76E-02	0	-1.52E+00
Inventory analyses	드			Halite	kg	9.06E+00	1.86E-07	0	1.48E+00	8.72E-03	-4.76E+00
jaj	·			Limestone	kg	7.02E+00	0	0	1.55E+00	5.64E-01	-5.96E+00
ā				Natural soda ash	kg	2.27E-01	0	0	0	0	-1.40E-01
S S	,		900	Wood	kg	1.38E+01	0	0	1.64E+01	0	-3.02E+01
ž			Pommen M	Water	kg	2.50E+04	3.33E+03	1.21E+00	3.08E+04	1.07E+02	-3.83E+03
Ne Ne	ent			CO2	kg	2.98E+02	3.45E+01	4.86E+01	4.31E+02	1.51E+01	-1.42E+02
=	Ĕ	to Atmosphere		Sox	kg	1.93E-01	2.61E-02	3.07E-02	2.44E-01	8.74E-03	-9.47E-02
	ō			Nox	kg	3.50E-01	2.09E-02	2.50E-01	4.26E-01	3.43E-02	-1.75E-01
	Ξ		ğ	N2O	kg	2.44E-02	4.96E-04	7.89E-03	5.98E-02	6.76E-05	-1.14E-02
	9		ĕ	CH4	kg	2.79E-03	7.96E-04	2.90E-07	5.77E-03	2.36E-05	-2.10E-04
	₽		ŧ	CO	kg	4.20E-02	5.07E-03	6.88E-02	8.53E-02	8.40E-03	-2.62E-02
	9 tc		0	NMVOC	kg	5.45E-03	1.56E-03	5.67E-07	1.13E-02	4.63E-05	-4.12E-04
	ırge		_	СхНу	kg	1.19E-02	1.03E-04	7.23E-03	1.43E-02	3.57E-04	-6.02E-03
	ha			Dust	kg	4.01E-02	1.13E-03	2.34E-02	2.89E-02	1.36E-03	-2.37E-02
	Disc	tem	nain	BOD	kg	-	-	-	-	-	-
	J/u	sys	dom	COD	kg	-	-	-	-	-	-
	Impact by Emission/Discharge to the environment	to Water system	o Water domain	N total	kg	-	-	-	-	-	-
	mis	Š	× ×	P total	kg	-	-	-	-	-	-
	ш	ρ		SS	kg	2.03E+00	4 245 00	- 0	6.07E-01	8.22E-01	7.005.04
	t b		system	Unspecified Solid Waste	kg		1.21E-06	0			-7.38E-01
	aci		il sy	Slag	kg	1.09E+01 3.92E-01	0	0	1.68E+00 8.66E-01	0	-1.08E+01 -1.25E+00
	m		io Soil	Sludge	kg	7.32E-01	2.08E-04	7.58E-08	1.51E-03	6.18E-06	-1.25E+00 -5.98E-05
±			7	Low level radio-active waste Energy resources (crude oil equivalent)	kg	9.87E+01	1.30E+01	1.52E+01	1.56E+02	8.27E-01	-3.96E-03 -4.08E+01
assessment	by Reso		and the same of th	Energy resources (crude oil equivalent) Mineral resources (Iron ore equivalent)	kg kg	7.59E+02	0	1.52E+01 0	1.75E+02	0.27E-01	-4.08E+01 -7.76E+02
SSn	- K		9	Global Warming (CO2 equivalent)	kg	3.05E+02	3.47E+01	5.07E+01	4.47E+02	1.52E+01	-1.45E+02
Se	envious		to Atmosphere	Acidification (SO2 equivalent)		4.38E-01	4.07E-02	2.06E-01	5.42E-01	3.28E-02	-2.17E-01
as	argeto		sou	Acidification (SOZ equivalent)	kg -	4.36E-01	4.07 E-02	2.00E-01	5.42E-01 -	3.20E-U2 -	-2.17E-01
act	on / Disc		o Atı	-	-	-		-	-	-	
Impact	yEnisie		-	-	-	-	-	-		-	-
=	£		_	-	_						

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts. Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore,
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero"
 - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

Product data sheet

_	(Input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	TOSHIBA TEC CORPORATION
EcoLEaf registration no.	AD-16-E763



Ī	PCR name	EP and IJ printer(PCR-ID:AD-04)	Product type	TOSHIBA MFP e-STUDIO3008A				
ı	LCA/LCIA in units of:	1	Product weight (kg)	54.9	Package (kg)	7.3	Weight total (kg)	62.2

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bre	eakdown of p	rimary materials		Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
	Ordinary steel	2.55E+01	Paper	6.50E+00	Press molding:Iron (kg)	2.90E+01	Parts assembly (kg)	1.08E+00	
	Stainless steel	3.53E+00	Semiconductor substrate	3.99E+00	Press molding:Nonferrous metal (kg)	7.18E+00			
بہ	Other metals	1.47E+00			Injection molding (kg)	2.61E+01			
Product	Aluminum	1.73E-01							
ĕ	Glass	1.86E+00							
Δ.	Thermoplastic resin	1.88E+01							
	Thermosetting resin	2.37E-01							
	Rubber	1.49E-01							
	Subtotal	5.17E+01	Subtotal	1.05E+01					
		Total		6.22E+01	Subtotal	6.22E+01	Subtotal	1.08E+00	

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

lo l	Classification	Energy	Energy	Energy	Material		
umpti	Distribution	Electricity (kWh)	Heavy oil as fuel (kg)	Furnace LPG (kg)	Industrial water (kg)		
onsur	Quantity	4.48E+00	1.00E-02	8.90E-02	3.20E-02		
Š	Note						
arge	Classification	Water system					
Oisch	Distribution	Sewage processing (kg)					
Non/	Quantity	3.20E-02					
Emiss	Note						

3.Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges,

-				, , , , , , , , , , , , , , , , , , , ,		,				
	ion	Means of transportation	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Diesel truck:10 ton (kg·km)			
≒	=	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
	strib	Quantity	6.22E+01	1.17E+04	1.00E+02	7.26E+05	6.22E+01	1.00E+03	4.48E+01	1.39E+05
	ä	Note								

Note The main body products are transported from China to USA.

4.Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	auot ana ao	ocosories subje	ct to tills allalys						
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Cold-Rolled steel	Stainless steel	Aluminum	Low density	Polystyrene	Polycarbonate	POM	PET
	Distribution	plate (kg)	plate (kg)	plate (kg)	polyethylene (kg)	(kg)	(kg)	(polyacetal) (kg)	(kg)
	Quantity	4.50E+00	1.30E+00	3.82E-01	6.50E-02	5.20E+00	1.20E-03	1.49E-01	9.11E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Process	Consumption
	Distribution	Expandable hard polyurethane (Hard) (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Blow molding (kg)	Freight by ship (kg·km)	Electricity (kWh)
	Quantity	1.04E+00	7.65E+00	3.45E-02	8.42E+00	5.63E+00	6.50E-02	1.38E+05	5.42E+02
Product	Note								
100	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Discharge
_	Distribution	Heavy oil as fuel (kg)	Gasoline as fuel (kg)	Furnace urban gas (13A) (m3)	Furnace LPG (kg)	Urban gas (13A) (m3)	Industrial water (kg)	Clean water (kg)	Sewage processing (kg)
	Quantity	1.00E-03	1.90E-02	1.51E+00	3.28E+01	1.05E+00	2.33E+00	3.46E+02	8.99E+01
	Note								
	Classification	Process							
	Distribution	Diesel truck: 4 ton (kg·km)							
	Quantity	4.97E+04							
	Note								

Note The periodical replacement parts are transported from China to USA.

4.2 Disposition/Recycle information on consumables and replacement

	Classification	Process	Process	Process	Process	Process	Process	Process	Process
parts ø	Distribution	Landfill: Industrial waste (kg)	Incineration: Industrial waste (kg)	Shredding (kg)	Recycle: to cold-rolled steel (kg)	Recycle: to Aluminum plate (kg)	Recycle: to Thermoplastic pellet (kg)	Recycle: to corrugated cardboard (kg)	Recycle: to Paper (kg)
les	Quantity	2.10E-01	2.92E+00	7.82E+00	5.80E+00	3.80E-01	3.32E+00	7.65E+00	3.00E-02
mables	Note								
	Classification	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	
Consi	Distribution	Cold-Rolled steel plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)	Polystyrene (kg)	Expandable hard polyurethane (Hard) (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	
	Quantity	4.50E+00	1.30E+00	3.80E-01	2.67E+00	5.40E-01	7.65E+00	3.00E-02	
	Note								

Dispu	isition/necy	cie stage inform	iation (per produ	ci). process mei	nou and scenari	US			
	Classification	Process	Process	Process	Process	Process	Process	Process	Process
	Distribution	Shredding (kg)	Landfill: Industrial waste (kg)	Incineration: Industrial waste (kg)	Diesel truck: 10 ton (kg·km)	Recycle: to cold-rolled steel (kg)	Recycle: to copper plate (kg)	Recycle: to Aluminum plate (kg)	Recycle: to Glass (kg)
	Quantity	3.94E+01	8.22E-01	8.71E+00	1.39E+04	3.02E+01	1.47E+00	1.73E-01	1.67E+00
	Note								
	Classification	Process	Process	Process	Deduction	Deduction	Deduction	Deduction	Deduction
Scenario	Distribution	Recycle: to Thermoplastic pellet (kg)	Recycle: to corrugated cardboard (kg)	Recycle: to Paper (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Copper plate (kg)	Aluminum plate (kg)	Glass (kg)
Š	Quantity	1.27E+01	6.45E+00	5.10E-02	2.55E+01	3.53E+00	1.47E+00	1.73E-01	1.67E+00
	Note								
	Classification	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction	
	Distribution	Polystyrene (kg)	Polycarbonate (kg)	Polycarbonate- ABS (70/30) (kg)	ABS (kg)	PET (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	
	Quantity	2.28E+00	9.12E-01	2.36E+00	2.81E+00	6.21E-01	6.45E+00	5.10E-02	
	Note								
Noto									

6. Others

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.