

Product Environmental Aspects Declaration



EP and IJ printer (PCR-ID:AD-04)

No. AD-17-E861
Date of publication
28/04/2017



ECOSYS M2640idw

<http://www.kyoceradocumentsolutions.co.jp/>


Contact us
KYOCERA Document Solutions Inc.
Corporate CSR Division
Product Environmental Planning Dep.
TEL : +81-6-6764-3760

Making Technology: Electrophotographic Printer (EP)
Printing Speed: Monochrome 40 Pages per minute in A4
Maximum printing paper: A4
Duplex function: Standard

【The Environmental load for life-cycle】

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO ₂ equivalent)	679kg (480kg)
Acidification (SO ₂ equivalent)	1.11kg (0.75kg)
Energy resources (crude oil equivalent)	15,274MJ (11,046MJ)

※Figures in () indicated environmental impact including recycle effect *note3



Use stage: Printing Mono 960,000

A4 sheets in 5 years.

The environmental load of sheet in "Use" stage is not included in above data.

Notes:

- Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Specification Criteria. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- Recycle Effect illustrates an indirect influence to other products/services.
- Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

- Conformed to the International ENERGY STAR® Program.
- Manufactured at ISO14001 certified factories.
- Plastic housing and outer package: halogenated flame retardants are not

PCR review was conducted by : PCR Deliberation Committee, January 01, 2008, Name of representative : Youji Uchiyama, Independent verification of the declaration and data, according to ISO14025:2006 <input type="checkbox"/> internal <input checked="" type="checkbox"/> external Third party verifier: Hiroo Sakazaki Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp
--

* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written. The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02Bs-02
Product vendor	KYOCERA Document Solutions Inc.
EcoLeaf registration no.	AD-17-E861

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	EP and IJ printer		Product type	ECOSYS M2640idw			
PCR code	AD-04	Product weight (kg)	20.5	Package (kg)	5.57	Weight total (kg)	26.07

In/Out items	Life Cycle Stage	Unit	Production		Distribution	Use	Disposition	Recycle Effect			
			Raw material	Product							
Energy Consumption											
		MJ	2.28E+03	4.25E+02	5.47E+01	1.24E+04	1.01E+02	-4.23E+03			
		Mcal	5.44E+02	1.02E+02	1.31E+01	2.97E+03	2.40E+01	-1.01E+03			
Inventory analyses	Impact by Resource Consumption	Exhaustible resources	Energy resources	Coal	kg	1.32E+01	2.72E+00	1.28E-04	4.83E+01	3.97E-02	-1.62E+01
				Crude oil (for fuel)	kg	2.38E+01	3.07E+00	1.20E+00	1.09E+02	2.09E+00	-4.41E+01
				LNG	kg	4.15E+00	1.42E+00	1.85E-02	3.04E+01	5.14E-02	-4.26E+00
				Uranium content of an ore	kg	4.20E-04	1.84E-04	8.67E-09	2.81E-03	2.69E-06	-1.98E-04
				Crude oil (for material)	kg	9.18E+00	0	0	4.50E+01	0	-3.16E+01
				Iron content of an ore	kg	7.83E+00	0	0	3.86E+00	0	-1.10E+01
				Cu content of an ore	kg	4.52E-01	0	0	2.38E-01	0	-1.03E+00
				Al content of an ore	kg	1.62E-01	0	0	8.82E-01	0	-9.89E-01
				Ni content of an ore	kg	7.22E-02	0	0	3.01E-01	0	-3.73E-01
				C content of an ore	kg	1.00E-01	0	0	4.09E-01	0	-5.09E-01
		Mineral resources	Mn content of an ore	kg	4.95E-02	0	0	6.89E-02	0	-6.22E-02	
			Pb content of an ore	kg	2.66E-02	0	0	1.93E-02	0	-8.34E-02	
			Sn content of an ore	kg	0	0	0	0	0	0	
			Zn content of an ore	kg	2.62E-01	0	0	1.90E-01	0	-8.19E-01	
			Au content of an ore	kg	0	0	0	0	0	0	
			Ag content of an ore	kg	0	0	0	0	0	0	
			Silica Sand	kg	1.05E+00	0	0	2.30E-01	0	-9.78E-01	
			Halite	kg	3.18E+00	0	0	3.01E+00	2.67E-04	-5.23E+00	
			Limestone	kg	2.01E+00	0	0	1.01E+00	1.73E-02	-2.03E+00	
			Natural soda ash	kg	1.00E-01	0	0	1.34E-02	0	-7.23E-02	
Wood	kg	1.18E+01	0	0	1.01E+02	0	-1.12E+02				
Water	kg	1.05E+04	2.06E+03	9.69E-02	4.22E+04	3.03E+01	-8.74E+03				
Impact by Emission/Discharge to the environment	to Atmosphere	CO2	kg	1.19E+02	2.11E+01	3.89E+00	5.11E+02	7.30E+00	-1.93E+02		
		Sox	kg	7.36E-02	1.61E-02	2.07E-03	3.44E-01	8.54E-03	-1.25E-01		
		Nox	kg	1.55E-01	1.28E-02	1.34E-02	6.74E-01	1.02E-01	-3.49E-01		
		N2O	kg	1.06E-02	2.33E-04	7.25E-04	4.85E-02	1.23E-04	-2.23E-02		
		CH4	kg	1.12E-03	4.92E-04	2.32E-08	7.49E-03	7.18E-06	-5.09E-04		
		CO	kg	1.50E-02	3.12E-03	2.47E-03	1.07E-01	3.91E-02	-2.54E-02		
		NMVOG	kg	2.19E-03	9.64E-04	4.54E-08	1.47E-02	1.41E-05	-9.95E-04		
		CxHy	kg	5.11E-03	5.07E-05	4.75E-04	1.62E-02	2.05E-03	-1.06E-02		
		Dust	kg	1.58E-02	6.91E-04	1.40E-03	4.51E-02	8.11E-03	-3.12E-02		
		to Water system	to Water domain	BOD	kg	-	1.73E-03	-	-	-	-
				COD	kg	-	-	-	-	-	-
				N total	kg	-	-	-	-	-	-
				P total	kg	-	-	-	-	-	-
		to Soil system	to Soil domain	Unspecified Solid Waste	kg	1.29E+00	6.79E-06	0	1.95E+01	8.74E-06	-2.70E+00
Slag	kg			3.07E+00	0	0	1.99E+00	0	-4.51E+00		
Sludge	kg			2.30E-01	0	0	1.89E+00	0	-2.12E+00		
Low level radio-active waste	kg			2.94E-04	1.28E-04	6.06E-09	1.96E-03	1.87E-06	-1.39E-04		
Impact assessment	by Res	to Atmosphere	Energy resources (crude oil equivalent)	kg	4.07E+01	8.03E+00	1.22E+00	2.00E+02	2.20E+00	-6.13E+01	
			Mineral resources (iron ore equivalent)	kg	1.83E+02	0	0	3.39E+02	0	-6.31E+02	
		to Atmosphere	Global Warming (CO2 equivalent)	kg	1.22E+02	2.12E+01	4.09E+00	5.24E+02	7.34E+00	-1.99E+02	
			Acidification (SO2 equivalent)	kg	1.82E-01	2.51E-02	1.14E-02	8.15E-01	7.99E-02	-3.69E-01	
			Ozone Depletion (CFC-11 equivalent)	kg	0	0	0	0	0	0	
			Photochemical Oxidant	kg	9.41E-03	7.11E-04	7.60E-04	3.10E-02	4.15E-03	-1.74E-02	
			Eutrophication (Phosphate equivalent)	kg	0	0	0	0	0	0	

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 - (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
 - Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
 - Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value, e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
 - B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
 - C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. We include package and attached articles, such as CD-ROM, operation manual in the product weight. Toner container as standard is included in the use stage, not in the product weight.
 2. Production stage: Environmental impacts on main product, toner supplied with and drum are included in this stage. Production of main product is included as China production. Toner and drum are included as Japan production.
 3. Transportation stage: Marine transport distance of a main product is 2,600km and domestic transport distance based on PCR provisions is 100km.
 4. Use stage: Based on PCR provision, impact on 960,000 sheets monochrome printing by user for five years is considered.
 5. Disposal/Recycle: We have calculated on the basis of a performance-based recycle scenario.
- This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03s-02
Product vendor	KYOCERA Document Solutions Inc.
EcoLeaf registration no.	AD-17-E861

PCR name	EP & IP Printer(PCR-ID:AD-04)	Product type	ECOSYS M2640idw				
LCA/LCIA in units of:	1 Unit	Product weight (kg)	20.5	Package (kg)	5.57	Weight total (kg)	26.07

1. Product information (per unit): parts etc. by material and by process/assembly method

Product	Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)			
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Carbon steel(kg)	6.75E+00	Paper (kg)	5.47E+00	Press molding:Iron (kg)	7.21E+00	Parts assembly (kg)	2.60E+01
	SUS (kg)	4.56E-01	Assembled circuit board (kg)	1.12E+00	Press molding:Nonferrous metal (kg)	6.23E-01		
	Cu (kg)	5.74E-01	Medium-sized motor (kg)	6.23E-01	Injection molding (kg)	1.00E+01		
	Al (kg)	1.01E-01			Blow molding (kg)	2.36E-02		
	Glass (kg)	8.62E-01			Glass molding (kg)	8.62E-01		
	Thermoplastics resin (kg)	1.00E+01						
	thermosetting resin (kg)	6.13E-02						
	Rubber (kg)	3.61E-02						
	Subtotal	1.89E+01	Subtotal	7.22E+00				
	Total		Subtotal	2.61E+01	Subtotal	1.88E+01	Subtotal	2.60E+01

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

Consumption	Classification	Energy	Material	Energy				
	Distribution	Electricity (kWh)	Industrial water (kg)	LNG (kg)				
	Quantity	2.42E+01	1.80E-01	5.62E-02				
	Note							
Emission/Discharge	Classification	Water system						
	Distribution	BOD						
	Quantity	1.73E-03						
	Note							

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Diesel truck:10 ton (kg·km)	Diesel truck:10 ton (kg·km)	Diesel truck:10 ton (kg·km)	Diesel truck:10 ton (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
	Quantity	2.61E+01	1.00E+02	5.63E+01	4.63E+03	2.61E+01	2.60E+03	1.00E+02	6.78E+04
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

Product	Classification	Process	Consumption	Consumption	Process	Process	Process	Process	Process
	Distribution	Diesel truck:2 ton (kg·km)	Electricity (kWh)	Industrial water (kg)	Press molding:Nonferrous metal (kg)	Injection molding (kg)	Blow molding (kg)	Parts assembly (kg)	Press molding:Iron(kg)
	Quantity	3.81E+04	5.69E+02	2.75E+02	9.01E-01	2.39E+01	1.70E-01	7.77E+01	5.02E+00
	Note								
Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Carbon steel(kg)	SUS (kg)	Cu (kg)	Al (kg)	Thermoplastics resin (kg)	Thermosetting resin (kg)	Rubber (kg)	Paper (kg)
	Quantity	3.12E+00	1.90E+00	5.41E-01	8.34E-01	5.65E+01	1.70E-01	6.50E-03	4.72E+01
	Note								
Product	Classification	Consumption							
	Distribution	Assembled circuit board (kg)							
	Quantity	5.42E-01							
	Note								

Note

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classification	Process	Process	Process	Process	Process	Process	Deduction	Deduction
	Distribution	Shredding (kg)	Recycle:to copper plate (kg)	Recycle:to Thermoplastic pellet (kg)	Recycle:to corrugated cardboard (kg)	Recycle:to cold-rolled steel (kg)	Recycle:to Aluminum plate (kg)	Carbon steel(kg)	SUS (kg)
	Quantity	7.80E+01	1.08E+00	2.39E+01	4.72E+01	5.02E+00	8.34E-01	3.12E+00	1.90E+00
	Note								
Consumables	Classification	Deduction	Deduction	Deduction	Deduction				
	Distribution	Cu (kg)	Al (kg)	Thermoplastics resin (kg)	Paper (kg)				
	Quantity	1.08E+00	8.34E-01	2.39E+01	4.72E+01				
	Note								

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

Scenario	Classification	Process	Process	Process	Process	Process	Process	Process	
	Distribution	Diesel truck:10 ton (kg·km)	Diesel truck:2 ton (kg·km)	Incineration: Industrial waste (kg)	Electricity (kWh)	Shredding (kg)	Recycle:to cold-rolled steel (kg)	Recycle:to copper plate (kg)	Recycle:to Aluminum plate (kg)
	Quantity	1.85E+03	3.81E+04	2.67E-01	6.80E-01	2.60E+01	7.21E+00	2.32E+00	1.01E-01
	Note								
Scenario	Classification	Process	Process	Process	Deduction	Deduction	Deduction	Deduction	
	Distribution	Recycle:to Thermoplastic pellet (kg)	Recycle:to corrugated cardboard (kg)	Recycle:to Glass (kg)	Carbon steel(kg)	SUS (kg)	Cu (kg)	Al (kg)	Glass (kg)
	Quantity	1.00E+01	5.47E+00	8.62E-01	6.75E+00	4.56E-01	2.32E+00	1.01E-01	8.62E-01
	Note								
Scenario	Classification	Deduction	Deduction						
	Distribution	Thermoplastics resin (kg)	Paper (kg)						
	Quantity	1.00E+01	5.47E+00						
	Note								

Note

6. Others

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.