# Product Environmental Aspects Declaration

EP and IJ printer (PCR number: AD-04)



## http://www.brother-usa.com/

For inquiry:

Environmental Product Group Production Innovation Dept. Production & Engineering Center Brother Industries, Ltd. Tel: +81-52-824-2511 (Representative) Fax: +81-52-824-5166



# 製品環境情報 http://www.jemai.or.jp

Date of publication Jun./05/2018


# Laser Printer HL-L5200DWT

# Specifications:

- Electrophotographic Printer (EP)
- Black & White
- Printing Speed: 40ppm (A4)
- Maximum Printing Size: Legal
- Wireless 802.11b/g/n, Ethernet, Hi-Speed USB 2.0
- Duplex Printing

The following data is calculated by assuming the product prints 960,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 22,900MJ
- Global warming impact (CO<sub>2</sub> equivalent) 1,344.2kg
- Acidification impact (SO<sub>2</sub> equivalent)
   2.09kg



· Electric power consumption in 5 years of "Use stage" is 463kWh.

The above data does not include the environmental impact of the paper that is used for printing.

## Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR:Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

# [Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School Independent verification of the label and data, according to ISO 14025 
internal external Third party verifier \*: System auditor, Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

\* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

# Product Environmental Information Data Sheet (PEIDS)



v2.1

Unit Function DB version

Characterization Factor DB version

Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AD-18-E1000

PCR name	EP(Electrophotographic Printer) an	Product type		HL-L52	HL-L5200DWT 7.95 Weight total (kg)		
PCR code	AD-04	Product weight (kg)	14.52	Package (kg)	7.95	Weight total (kg)	22.47

			_	Life Cycle Stage		Produ	uction				
In/Ou	ut iten	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Total
					MJ	1.91E+03	2.09E+02	7.40E+01	2.07E+04	2.36E+01	2.29E+04
		Er	nergy C	Consumption	Mcal	4.56E+02	4.99E+01	1.77E+01	4.95E+03	5.64E+00	5.47E+03
	f Coal		ka	8.61E+00	1.33E+00	1.73E-04	8.87E+01	1.44E-01	9.88E+01		
			sourc	Crude oil (for fuel)	ka	2.04E+01	1.64E+00	1.62E+00	1.94E+02	2.48E-01	2.18E+02
			ay ree	LNG	ka	3.51E+00	6.91E-01	2.50E-02	3.86E+01	7.42E-02	4.29E+01
			inerç	Uranium content of an ore	kg	3.34E-04	9.03E-05	1.17E-08	4.01E-03	9.76E-06	4.45E-03
	ç	-		Crude oil (for material)	kg	9.00E+00	3.45E-03	0	8.87E+01	0	9.77E+01
	tio	<i>(</i> 0		Iron content of an ore	kg	4.35E+00	0.402.00	0	3.07E+01	Ő	3.50E+01
	đ	) Se		Cu content of an ore	kg	2.21E-01	0	Ő	4.92E-02	Ő	2.70E-01
	sul	nr		Al content of an ore	kg	1.09E-01	0	0	1.51E+00	Ő	1.62E+00
	ü	So	S	Ni content of an ore	kg	1.27E-02	0	Ő	1.89E-01	Ő	2.02E-01
	Õ	Le	ce	C content of an ore	kg	1.85E-02	0	0	2.67E-01	0	2.85E-01
	ce	ole	'n	Mn content of an ore	kg	2.22E-02	Ő	Ő	1.92E-01	Ő	2.14E-01
	our	stil	resources	Pb content of an ore	kg	9.85E-03	0	Ő	1.35E-03	Ő	1.12E-02
	by Resource Consumption	Exhaustible resources	E E	Sn content of an ore	kg	-	-	-	-	-	
	Å	Ť.	Mineral	Zn content of an ore	kg	9.70E-02	0	0	1.33E-02	0	1.10E-01
	ą	ш	ine	Au content of an ore	kg	-	-	-	-	-	
	Impact I		Σ	Ag content of an ore	kg	-	-	-	-	-	
S	ра			Silica Sand	kg	3.43E-01	0	0	4.72E-01	0	8.16E-01
anaiyses	<u></u>			Halite	kg	1.96E+00	4.74E-05	0	7.93E+00	5.83E-03	9.90E+00
ai				Limestone	kg	1.10E+00	3.07E-03	0	9.79E+00	2.09E-01	1.11E+01
an				Natural soda ash	kġ	2.95E-02	0	0	1.26E-02	0	4.22E-02
ry				Wood	kġ	1.58E+01	8.53E-02	0	1.87E+02	0	2.03E+02
Inventory				Water	kg	8.69E+03	1.02E+03	1.31E-01	6.26E+04	1.23E+02	7.24E+04
ve	nt			CO2	kg	9.53E+01	1.09E+01	5.25E+00	1.19E+03	2.25E+01	1.32E+03
느	me	Φ		Sox	kg	5.42E-02	8.07E-03	3.31E-03	7.03E-01	1.18E-02	7.80E-01
	uo.		le	Nox	kg	1.32E-01	7.20E-03	2.69E-02	1.68E+00	2.48E-02	1.87E+00
	iž	-	Ld.	N2O	kg	8.74E-03	2.83E-04	8.55E-04	7.47E-02	2.95E-05	8.46E-02
	e		SO	CH4	kg	8.93E-04	2.42E-04	3.13E-08	1.07E-02	2.61E-05	1.19E-02
	th€		t t	CO	kg	1.08E-02	1.62E-03	7.39E-03	2.37E-01	4.45E-03	2.61E-01
	to		o Atmosphere	NMVOC	kg	1.75E-03	4.73E-04	6.13E-08	2.09E-02	5.12E-05	2.32E-02
	ge		÷	CxHy	kg	4.17E-03	7.33E-05	7.80E-04	3.84E-02	7.73E-05	4.35E-02
	hai			Dust	kg	1.23E-02	3.99E-04	2.53E-03	1.33E-01	1.40E-03	1.50E-01
	impact by Emission/Discharge to the environment	em	lain	BOD	kg	-	-	-	-	-	
	Ę	syst	mop	COD	kg	-	-	-	-	-	
	sion	to Water system	Water domain	N total	kg	-	-	-	-	-	
	lis	Wa	Wa	P total	kg	-	-	-	-	-	
	Εu	9	9	SS	kg	-	-	-	-	-	
	by		stem	Unspecified Solid Waste	kg	1.22E+00	1.08E-03	0	7.39E+01	7.30E+00	8.24E+01
	act		Soil systen	Slag	kg	1.48E+00	0	0	9.39E+00	0	1.09E+01
	npś		Soi	Sludge	kg	1.39E-01	0	0	3.20E+00	0	3.34E+00
	-		to	Low level radio-active waste	kg	2.34E-04	6.31E-05	8.19E-09	2.80E-03	6.82E-06	3.10E-03
nent	les out e auerpt in	Exhaustib	ole resources	Energy resources (crude oil equivalent)	kg	3.29E+01	4.07E+00	1.65E+00	3.30E+02	5.10E-01	3.69E+02
essn	te P Oce		_	Mineral resources (Iron ore equivalent)	kg	6.79E+01	1.90E-03	0	2.45E+02	0	3.13E+02
t ass	sion / ge to ment	to Atm	osphere	Global Warming (CO2 equivalent)	kg	9.76E+01	1.10E+01	5.48E+00	1.21E+03	2.25E+01	1.34E+03
np act	by Emiss Discharg environ			Acidification (SO2 equivalent)	kg	1.47E-01	1.31E-02	2.21E-02	1.88E+00	2.91E-02	2.09E+00
F	200				kg						

[Notes for readers: EcoLeaf common rules]

I. Stage related

A. "Production" stage is intended for two sub-stages listed below.

(1) "Raw material" production: consists of mining, transportation and raw material production.

(2) "Product" production: consists of the parts processing, assembly and installation.

B. "Distribution" stage is intended for transportation of produced product, Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.

C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts)

D. "Disposition" stage is intended for environmental impacts by product disposition.

II Inventory analyses

A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.

B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel. C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO<sub>2</sub> in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

A. Exponential notation, after the decimal point to two, should be used.

B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate " - " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

D. Row total of the data is automatically calculated, excluding a row includes " - " item. Row total of such is presented as a blank (no data) (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

#### [Notes for readers: Target product specific]

1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags). 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.

3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.

The transportation distance in Japan uses 100 kmas average distance

4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 960,000 sheets, calculated by supposing a user use a machine for 5 years,

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.


Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables 5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

#### Product data sheet





	PCR name	E	EP and IJ prir	nter(PCR ID:AD-04)	Product t	уре			HL-L5200DWT				
LCA	CA/LCIA in units of: 1 Product weight (kg) 14.52 Package (kg) 7.95 Weight total (							Weight total (kg)	22.47				
1. Prod	luct information (p	per unit): p	arts etc. by	material and by process/as	ssembly me	thod							
		reakdown of pa	arts, which n	ed to apply	Process	sing / Assembly Base Un	its (Parts B, C)						
	Material na	ame	Weight (kg)	Material name	Weight (kg)	P	Process nam	ie W	eight (kg)		Process name	Weight (kg)	
	Steel		3.64E+00	Semiconductor substrate	8.80E-01	Press	molding:litor	n (kg) 🛛 3	.72E+00	Pa	rts assembly (kg)	1.82E+00	
	Stainless steel		7.98E-02	Medium-sized motor	5.03E-01	Press molding:Nonferrous metal (kg)		ietal (kg)	.80E-02				
+	Aluminum		6.14E-02	Lubricants	1.07E-02	Injection molding (kg)		g (kg) 🛛 S	72E+00				
duct	Thermoplasti	c resin	9.60E+00			Gla	iss molding	(kg) 9	.17E-02				
2	Thermosettin	g resin	2.97E-02										
ā	Rubber	•	1.79E-01										
	Glass		9.17E-02										
	Paper		7.40E+00										
	Subtota		2.11E+01	Subtotal	1.39E+00								
			Total		2.25E+01		Subtotal	1	.36E+01		Subtotal	1.82E+00	

Note

### 2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Material
	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 10 ton (kg.km)	LNG as fuel (kg)	Diesel oil as fuel (kg)	Heavy oil fuel (kg)	Freight by ship (kg.km)	Raw wood (foreign) (kg)
ion	Quantity	3.66E-02	9.34E+00	1.38E+01	2.07E-02	1.82E-02	4.86E-02	4.81E+02	7.38E-03
Consumption	Note								
Insu	Classification	Material	Energy	Energy	Energy	Material			
Cor	Distribution	Low density polyethylene (kg)	LPG(NPG) as fuel (kg)	Incineration: Industrial waste (kg)	Diesel truck: 20 ton (kg.km)	PP (kg)			
	Quantity	1.14E-03	3.47E-02	4.74E-02	7.07E+01	2.32E-03			
	Note								
arge	Classification								
Disch	Distribution								
Emission/	Quantity								
Emis	Note								
Note									

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Freight by ship (kg.km) Load (kg·km) 7.87E+04
7.87E+04

Note

#### 4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Organization	Oraciantica	Organization	Orangentian	Organization	Ormania	Ormania	Ormania
		Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Cold-Rolled steel plate (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)
	Quantity	4.63E+02	6.96E+04	7.41E+05	9.94E+04	1.17E-01	2.89E+01	1.19E+00	1.41E+00
	Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Glass (kg)	High density polyethylene (kg)	Low density polyethylene (kg)	PP (kg)	PA66 (Polyamide 66) (kg)	PS (kg)	PBT(Poly Butylene Terephtalate) (kg)	Polycarbonate (kg)
	Quantity	1.15E-01	1.54E-02	4.27E+00	3.86E+00	1.92E-02	3.92E+01	1.93E-02	2.63E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	PC-ABS(70/30)(kg)	POM(polyacetal) (kg)	ABS (kg)	AS resin (kg)	MMA resin (kg)	PET (kg)	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)
	Quantity	4.73E-01	4.28E+00	5.72E+00	2.76E+01	1.86E-01	3.40E+00	1.74E+00	1.10E+00
duct	Note								
Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Corrugated cardboard (kg)	Paper (Western style)	Assembled circuit board(kg)	Medium-sized motor (kg)	Press molding: Iron (kg)	Press molding: Norferrous metal (kg)	Injection molding (kg)	Glass molding (kg)
	Quantity	8.39E+01	1.29E+00	1.21E-01	1.64E-01	3.02E+01	6.74E-02	6.66E+01	1.15E-01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Process
	Distribution	Parts assembly (kg)	Electricity (kwh)	Heavy oil fuel (kg)	Diesel oil as fuel (kg)	LPG(NPG) as fuel (kg)	LNG as fuel (kg)	Raw wood (foreign) (kg)	Incineration: Industrial waste (kg)
	Quantity	1.04E+01	2.54E+02	1.52E+01	2.65E-01	5.03E-01	6.42E-01	2.29E-01	3.95E+00
	Note		Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption		
	Distribution	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Corrugated cardboard (kg)	Low density polyethylene (kg)	PP (kg)		
	Quantity	2.19E+03	1.01E+05	4.31E+03	2.64E+00	3.59E-01	7.28E-01		
	Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years		

Note Electric power consumption in 5 years of "Use stage" is 463kWh.

4.2 DI3	position/ite	cycle informatio	II OII COII3uillabi	es and replacem	ent parts		
les	Classification	Consumption	Process	Process	Process		
nab	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to 1 andfill	Landfill: General waste (kg)		
Insu	Quantity	2.06E+04	1.13E+02	1.76E+02	3.73E+01		
ē	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected		
Note							

#### 5. Disposition/Recycle stage information (per product): process method and scenarios

.e	Classification	Consumption	Process	Process	Process		
Jari	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to 1 andfill	Landfill: General waste (kg)		
cer	Quantity	2.05E+03	1.33E+01	1.65E+01	4.74E+00		
s	Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected		
Note							