Product Environmental Aspects Declaration



EP and IJ printer (PCR-ID:AD-04)

No. AD-19-E1161 Date of publication 09/24/2019

TOSHIBA

TOSHIBA TEC CORPORATION Corporate Quality & Environmental Group TEL: +81-3-6830-9100

E-STUDIO2822AF

1. Printing Process: Electrophotography (EP)

2. Color: Monochrome(B/W)

3. Printing Speed: 28 Letter pages per minute (B/W)


4. Maximum Paper Size: Ledger Size

5. Duplex copying: Standard



Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO ₂ equivalent)	579.4kg (552.6kg)
Acidification (SO_2 equivalent)	1.30kg (1.25kg)
Energy resources (crude oil equivalent)	10,746MJ (10,161MJ)

*Figures in () indicated environmental impact including recycle effect *note3



The above environmental load is calculated assuming that the usage period is 5 years and the total number of printed sheets is 470,400 pages. Also, the printing paper is not included in the calculation range.

Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule.
 Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf_jemai.jp/eng/ for details.
- ${\it 3. \,\, Recycle \,\, Effect \,\, illustrates \,\, an \,\, indirect \,\, influence \,\, to \,\, other \,\, products/services.}$
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 5. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

- ·Certified to the international ENERGY STAR Program V3.0, EU RoHS
- Manufactured at ISO14001 certified factories

PCR review was conducted by : PCR Deliberation Committee, January 01,2008, Name of representative: Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025:2006 □internal ■external

Third party verifier: Yasuo Koseki

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

The Ecoleaf is an environmental labeling program that belongs to the ISO-Type III category.

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02Bs-02
Product vendor	TOSHIBA TEC CORPORATION
EcoLeaf registration no.	AD-19-E1161

Unit Function DB version Characterization Factor DB version

map://www.jemanerijp
v2.1
v2.1

PCR name	EP and IJ print	Product type	TOSHIBA MFP e-STUDIO2822AF				
PCR code	AD-04	Product weight (kg)	24.4	Package (kg)	5.4	Weight total (kg)	29.8

			Life Cycle Sta	ge	Prod	uction	51.11.11		5	Recycle
In/O	ut iter	ns		Unit	Raw material	Product	Distribution	Use	Disposition	Effect
	Energy Consumption			MJ	2.47E+03	3.00E+02	4.75E+02	7.46E+03	3.69E+01	-5.86E+02
		Lileig	y Consumption	Mcal	5.91E+02	7.17E+01	1.13E+02	1.78E+03	8.82E+00	-1.40E+02
			ဖ္စ Coal	kg	1.33E+01	2.06E+00	1.11E-03	2.86E+01	1.54E-01	-3.94E+00
		erg	Crude oil (for fuel)	kg	2.40E+01	2.41E+00	1.04E+01	6.96E+01	5.20E-01	-4.39E+00
		Energy	g LNG	kg	4.56E+00	1.14E+00	1.60E-01	1.61E+01	8.32E-02	-4.04E-01
			Chamber Contont of all o		3.93E-04	1.40E-04	7.51E-08	1.66E-03	1.04E-05	-1.14E-05
	_		Crude oil (for material		1.31E+01	0	0	2.48E+01	0	-5.28E+00
	l ö	Se	Iron content of an ore	kg	8.68E+00	0	0	3.22E+00	0	-3.77E+00
	j 전	<u>ĕ</u>	Cu content of an ore Al content of an ore	kg	5.50E-01 2.48E-01	0	0	7.46E-03 5.98E-01	0	-8.38E-02 -3.02E-01
	5	00	Ni content of an are	kg kg	4.47E-02	0	0	3.90E-03	0	-7.67E-05
	Consumption	Exhaustible resources	C content of an ore	kg	6.31E-02	0	0	6.40E-03	0	-1.40E-03
	ပြ	e E	Mn content of an ore	kg	4.74E-02	0	0	1.77E-02	0	-1.42E-03
	Se] } }	Pb content of an ore	kg	2.84E-02	0	0	6.05E-04	0	-6.81E-03
	Resource	ag e	ISD CONTANT OF 3D OFA	kg	0	0	0	0.002 01	0	0.012 00
) 	🛱 📶	Zn content of an ore	kg	2.79E-01	0	0	5.96E-03	0	-6.69E-02
		Exha	Au content of an ore	kg	0	0	0	0	0	0
	by	Σ	Ag content of an ore	kg	0	0	0	0	0	0
	Impact		Silica Sand	kg	1.01E+00	0	0	5.19E-02	0	-2.71E-01
S	ba		Halite	kg	6.99E+00	1.18E-04	0	1.23E+00	1.01E-02	-2.05E+00
se	<u></u>		Limestone	kg	2.04E+00	0	0	1.82E+00	3.90E-01	-6.96E-01
aiy			Natural soda ash	kg	9.39E-02	0	0	1.34E-03	0	-2.59E-02
ry anaiyses		Renewable	Wood	kg	7.70E+00	0	0	2.34E+01	0	0
Inventory		Rene	Water	kg	9.27E+03	1.58E+03	8.32E-01	2.60E+04	1.30E+02	-7.48E+02
Ĺ	at l		CO ₂	kg	1.22E+02	1.63E+01	3.36E+01	3.74E+02	2.27E+01	-2.59E+01
	environment	d)	SOx	kg	7.59E-02	1.23E-02	2.74E-02	2.64E-01	1.25E-02	-2.12E-02
	Ϊ́	l e	NOx	kg	1.62E-01	1.02E-02	2.80E-01	8.05E-01	3.73E-02	-4.25E-02
	2	l di	N ₂ O	kg	1.25E-02	3.01E-04	3.96E-03	2.40E-02	5.38E-05	-3.48E-03
	e e	Atmosphere	CH₄	kg	1.05E-03	3.73E-04	2.01E-07	4.43E-03	2.79E-05	-2.51E-05
	to the	-} 	CO	kg	1.53E-02	2.48E-03	9.63E-02	2.04E-01	8.73E-03	-4.69E-03
	ĕ	0	NMVOC	kg	2.05E-03	7.31E-04	3.93E-07	8.67E-03	5.48E-05	-4.94E-05
	arg		СхНу	kg	5.81E-03	6.71E-05	6.67E-03	1.84E-02	3.07E-04	-1.69E-03
	ដូ		Dust	kg	1.75E-02	5.60E-04	2.39E-02	6.64E-02	1.97E-03	-5.73E-03
	Dis		BOD	kg	-	-	-	-	-	-
	Į Ž		⊆ COD	kg	-	-	-	-	-	-
	Emission/Discharge	to Water system to Water	N total	kg	-	-	-	-	-	-
	E i	5 8	P total	kg	-	-	-	-	-	-
			55	kg	4.005.00	- 0.005.04	-	- 0.005.00	0.445.00	- 0.505.04
	Impact by	<u>≔</u> E	Unspecified Solid Wast		1.30E+00	6.60E-04	0	6.08E+00	9.11E+00	-2.50E-01
	Dac	to Soil system	Slag	kg	3.24E+00 3.41E-01	0	0	9.95E-01 1.28E+00	0	-1.22E+00 -6.49E-01
	<u>E</u>	to	Sludge Low level radio-active wast	kg e kg	2.75E-04	9.75E-05	5.26E-08	1.28E+00 1.16E-03	7.30E-06	-8.06E-06
			Energy resources (crude oil equivalent)	kg	4.13E+01	6.24E+00	1.06E+01	1.21E+02	8.04E-01	-7.49E+00
ment	by Resource Consumption	Exhaustible resources	Mineral resources (Iron ore equivalent)	kg	1.80E+02	0	0	2.39E+01	0	-3.26E+01
sesa		ø	Global Warming (CO ₂ equivalent)	kg	1.25E+02	1.64E+01	3.47E+01	3.81E+02	2.27E+01	-2.68E+01
mpact	by Emission / Discharge to	to Atmosphere	Acidification (SO ₂ equivalent)	kg	1.89E-01	1.94E-02	2.24E-01	8.27E-01	3.85E-02	-5.10E-02
) Sisc	0	-	-	-	-	-	-	-	-
	ام فا	<u> </u>	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-
Note	e for re	adore: Ecol o	af common rules]							

- I. Stage related
- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse. Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts. Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
 - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

Product data sheet

(Input data and parameters for LCA)

	(input data and parameters for EON)
Document control no.	F-03s-02
Product vendor	TOSHIBA TEC CORPORATION
EcoLEaf registration no.	AD-19-E1161



PCR name	EP and IJ printer (PCR-ID:AD-04)	Product type	TOSHIBA MFP e-STUDIO2822AF				
LCA/LCIA in units of:	1	Product weight (kg)	24.4	Package (kg)	5.4	Weight total (kg)	29.8

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bro	eakdown of pr	imary materials	Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Ordinary steel	7.22E+00	Paper	3.60E+00	Press molding: Iron (kg)	7.32E+00	Parts assembly (kg)	1.20E-01
	Stainless steel	2.82E-01	Wood	6.00E-04	Press molding: Nonferrous metal (kg)	4.53E+00		
<u>c</u>	Other metals 7.72E-01		Semiconductor substrate	8.49E-01	Injection molding (kg)	1.50E+01		
Product	Aluminum 1.50E-01		Medium-sized motor	1.01E+00	Glass molding (kg)	8.68E-01		
Pro	Glass	8.68E-01						
	Thermoplastic resin	1.45E+01						
	Thermosetting resin	1.28E-01						
	Rubber	3.77E-01						
	Subtotal	2.43E+01	Subtotal	5.46E+00				
		Total		2.98E+01	Subtotal	2.77E+01	Subtotal	1.20E-01

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

	Classification	Energy	Energy	Energy	Energy	Energy	Material	Material	Material
Consumption	Distribution	Heavy oil as fuel (kg)	Furnace LPG (kg)	Electricity (kWh)	Urban gas (13A) (m3)	Furnace urban gas (13A) (m3)	Industrial water (kg)	Clean water (kg)	Diesel truck: 4 ton (kg·km)
	Quantity	7.00E-03	4.40E-02	4.55E+00	1.14E-01	1.90E-02	1.50E+01	5.66E+00	1.44E+02
	Note								
Inst	Classification	Material							
Col	Distribution	Freight by ship (kg·km)							
	Quantity	7.24E+02							
	Note								
ırge	Classification	Water system							
Emission/Discharge	Distribution	Sewage processing (kg)							
ssion	Quantity	2.03E+01							
Ë	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 10 ton (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)			
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
8	Quantity	2.98E+01	6.00E+01	5.00E+01	3.57E+03	2.98E+01	1.17E+04	1.00E+02	3.48E+05
inc	Note								
Distribution	Means of transportation	Diesel truck: 10 ton (kg·km)							
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)				
	Quantity	2.98E+01	3.30E+03	5.00E+01	1.97E+05				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

<u> </u>	duct and ac	cessories subje	ct to this analysi	3					
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Cold-Rolled steel plate (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)	Low density polyethylene (kg)	Polypropylene (kg)	Polystyrene (kg)	PBT (kg)
	Quantity	1.30E+00	1.80E+00	2.43E-02	5.65E-01	3.30E-02	2.17E-02	1.79E+01	1.90E-02
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	POM (polyacetal) (kg)	PET (kg)	Expandable hard polyurethane (Hard) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Styrene- butadiene rubber (SBR) (kg)	Corrugated cardboard (kg)	Paper (Western style) (kg)	Assembled circuit board (kg)
#	Quantity	2.80E-01	9.24E+00	8.24E-01	3.50E-03	9.70E-02	1.09E+01	1.14E-01	5.40E-02
əp	Note								
Product	Classification	Consumption	Consumption	Consumption	Process	Process	Consumption	Consumption	Consumption
	Distribution	Press molding: Iron (kg)	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Freight by ship (kg·km)	Diesel truck: 4 ton (kg·km)	Electricity (kWh)	Heavy oil as fuel (kg)	Furnace LPG (kg)
	Quantity	1.82E+00	1.15E+01	1.92E+01	5.96E+05	2.36E+05	3.68E+02	8.40E-04	5.38E-03
	Note				_				

Classification	Consumption	Consumption	Consumption	Consumption	Discharge		
Distribution	Urban gas (13A) (m3)	Furnace urban gas (13A) (m3)	Industrial water (kg)	Clean water (kg)	Sewage processing (kg)		
Quantity	1.25E+00	1.33E-01	2.73E+01	4.74E+01	1.05E+02		
Note							

Note

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classification	Process	Process	Process	Process	Process	Process	Process	Process
	Distribution	Shredding (kg)	Landfill: Industrial waste (kg)	Incineration: Industrial waste (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)	Diesel truck: 4 ton (kg·km)	Sorting: Iron (by magnetic force) (kg)	Sorting: Nonferrous metal (by eddy current with wind force) (kg)
	Quantity	3.40E+01	4.38E-01	1.01E+01	1.82E+01	2.21E+00	1.10E+04	9.21E+00	7.96E+00
	Note								
	Classification	Process	Process	Process	Process	Deduction	Deduction	Deduction	
	Distribution	Sorting: Plastics (by relative density difference in water) (kg)	Recycle: to cold-rolled steel (kg)	Recycle: to Aluminum plate (kg)	Recycle: to Thermoplastic pellet (kg)	Cold-Rolled steel plate (kg)	Aluminum plate (kg)	Polystyrene (kg)	
	Quantity	7.74E+00	1.19E+00	2.26E-01	6.52E+00	1.07E+00	2.26E-01	1.78E+00	
	Note								

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

. <u> </u>	, , , , , , , , , , , , , , , , , , , ,	role stage illielli	ation (per produ	oty: process met	nou and Scenario				
Scenario	Classification	Process	Process	Process	Process	Process	Process	Process	Process
	Distribution	Landfill: Industrial waste (kg)	Incineration: Industrial waste (kg)	Shredding (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)	Diesel truck: 10 ton (kg·km)	Diesel truck: 4 ton (kg·km)	Sorting: Iron (by magnetic force) (kg)
	Quantity	1.11E+00	3.73E+00	2.98E+01	1.17E+01	6.18E+00	9.76E+03	1.73E+03	1.01E+01
	Note								
	Classification	Process	Process	Process	Process	Process	Process	Process	Deduction
	Distribution	Sorting: Nonferrous metal (by eddy current with wind force) (kg)	Sorting: Plastics (by relative density difference in water) (kg)	Recycle: to cold-rolled steel (kg)	Recycle: to copper plate (kg)	Recycle: to Aluminum plate (kg)	Recycle: to Glass (kg)	Recycle: to Thermoplastic pellet (kg)	Cold-Rolled steel plate (kg)
	Quantity	7.12E+00	6.76E+00	2.85E+00	2.78E-01	6.00E-02	3.09E-01	5.16E+00	2.57E+00
	Note								
	Classification	Deduction	Deduction	Deduction	Deduction	Deduction	Deduction		
	Distribution	Copper plate (kg)	Aluminum plate (kg)	Polystyrene (kg)	Polycarbonate- ABS (70/30) (kg)	ABS (kg)	Glass (kg)		
	Quantity	2.78E-01	6.00E-02	1.40E+00	1.99E+00	4.69E-01	3.09E-01		
	Note								

Note

6. Others

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.