

Product Environmental Aspects Declaration



EP and IJ Printer (PCR-ID:AD-04)

No. AD-20-E1183



Date of publication
2/3/2020

TASKalfa 8353ci

<http://www.kyoceradocumentsolutions.co.jp/>

Contact us
KYOCERA Document Solutions Inc.
CSR Division
Product Environmental Planning Dep.
TEL : +81-6-6764-3760

Making Technology: Electrophotographic Printer (EP)
Printing Speed: Monochrome 83 Pages per minute in A4
Color 70 Pages per minute in A4
Maximum printing paper: A3
Duplex function: Standard




【The Environmental load for life-cycle】

| Consumption and discharge in a life cycle | All the stage sum totals |
|---|--------------------------|
| Global Warming (CO ₂ equivalent) | 3107kg (2021kg) |
| Acidification (SO ₂ equivalent) | 5.1kg (2.9kg) |
| Energy resources (crude oil equivalent) | 64,843MJ (43,792MJ) |

※Figures in () indicated environmental impact including recycle effect *note3

Warming load CO₂ equivalent of each stage[kg]



Use stage: Printing Mono 2066700/Color 1470000
A4 sheets in 5 years.

The environmental load of sheet in "Use" stage is not included in above data.

Notes:

- Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Specification Criteria. Visit EcoLeaf website under homepage at <http://www.ecoleaf-jemal.jp/eng/pcr.html> for detail. for details.
- Recycle Effect illustrates an indirect influence to other products/services.
- Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

- Conformed to the International ENERGY STAR® Program .
- Manufactured at ISO14001 certified factories.
- Plastic housing and outer package: halogenated flame retardants are not used.

PCR review was conducted by : PCR Deliberation Committee, January 01, 2008, Name of representative : Youji Uchiyama,
Independent verification of the declaration and data, according to ISO14025:2006 internal external
Third party verifier: < name of the third party verifier * > Hiroo Sakazaki
Programme operator Sustainable Management Promotion Organization ecoleaf@sumpo.or.jp

* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

Product Environmental Information Data Sheet (PEIDS)



| | |
|--------------------------|---------------------------------|
| Document control no. | F-02Bs-02 |
| Product vendor | KYOCERA Document Solutions Inc. |
| EcoLeaf registration no. | AD-20-E1183 |

| | |
|------------------------------------|------|
| Unit Function DB version | v2.1 |
| Characterization Factor DB version | v2.1 |

| | | | | | | | |
|----------|-------------------|---------------------|--------------|-----------------|------|-------------------|-------|
| PCR name | EP and IJ Printer | | Product type | TASKalfa 8353ci | | | |
| PCR code | AD-04 | Product weight (kg) | 186.8 | Package (kg) | 38.3 | Weight total (kg) | 225.1 |

| In/Out items | Life Cycle Stage | Unit | Production | | Distribution | Use | Disposition | Recycle Effect | | | |
|---|--------------------------------|---|------------------------------|---------------------------|--------------|----------|-------------|----------------|-----------|-----------|-----------|
| | | | Raw material | Product | | | | | | | |
| Energy Consumption | | | | | | | | | | | |
| | | MJ | 1.75E+04 | 2.22E+03 | 4.90E+02 | 4.44E+04 | 2.17E+02 | -2.11E+04 | | | |
| | | Mcal | 4.17E+03 | 5.30E+02 | 1.17E+02 | 1.06E+04 | 5.17E+01 | -5.03E+03 | | | |
| Inventory analyses | Impact by Resource Consumption | Energy resources | Coal | kg | 1.52E+02 | 1.56E+01 | 1.14E-03 | 1.96E+02 | 3.02E-01 | -1.67E+02 | |
| | | | Crude oil (for fuel) | kg | 1.61E+02 | 1.79E+01 | 1.07E+01 | 3.78E+02 | 4.13E+00 | -1.81E+02 | |
| | | LNG | kg | 3.28E+01 | 7.80E+00 | 1.65E-01 | 1.12E+02 | 2.11E-01 | -2.55E+01 | | |
| | | Exhaustible resources | Mineral resources | Uranium content of an ore | kg | 3.25E-03 | 1.05E-03 | 7.76E-08 | 9.50E-03 | 2.05E-05 | -8.72E-04 |
| | | | | Crude oil (for material) | kg | 5.57E+01 | 0 | 0 | 1.63E+02 | 0 | -1.31E+02 |
| | | | | Iron content of an ore | kg | 1.12E+02 | 0 | 0 | 3.44E+01 | 0 | -1.37E+02 |
| | | | | Cu content of an ore | kg | 3.80E+00 | 0 | 0 | 5.67E-01 | 0 | -6.88E+00 |
| | | | | Al content of an ore | kg | 5.33E+00 | 0 | 0 | 1.03E+01 | 0 | -1.49E+01 |
| | | | | Ni content of an ore | kg | 6.17E-01 | 0 | 0 | 8.28E-01 | 0 | -1.45E+00 |
| | | | | C content of an ore | kg | 8.71E-01 | 0 | 0 | 1.13E+00 | 0 | -2.00E+00 |
| | | | | Mn content of an ore | kg | 6.50E-01 | 0 | 0 | 3.08E-01 | 0 | -3.22E-01 |
| | | | | Pb content of an ore | kg | 1.89E-01 | 0 | 0 | 3.22E-02 | 0 | -5.70E-01 |
| | | | | Sn content of an ore | kg | 0 | 0 | 0 | 0 | 0 | 0 |
| | | | | Zn content of an ore | kg | 1.88E+00 | 0 | 0 | 3.69E-01 | 0 | -5.67E+00 |
| | | | | Au content of an ore | kg | 0 | 0 | 0 | 0 | 0 | 0 |
| | | | | Ag content of an ore | kg | 0 | 0 | 0 | 0 | 0 | 0 |
| | | | | Silica Sand | kg | 5.37E+00 | 0 | 0 | 7.82E-01 | 0 | -4.45E+00 |
| | | Halite | kg | 2.92E+01 | 0 | 0 | 1.01E+01 | 2.38E-02 | -3.33E+01 | | |
| | | Limestone | kg | 2.42E+01 | 0 | 0 | 7.20E+00 | 1.54E+00 | -2.36E+01 | | |
| | | Natural soda ash | kg | 3.97E-01 | 0 | 0 | 3.58E-02 | 0 | -1.91E-01 | | |
| | | Impact by Emission/Discharge to the environment | to Atmosphere | Wood | kg | 5.17E+01 | 0 | 0 | 2.86E+02 | 0 | -3.16E+02 |
| | | | | Water | kg | 8.34E+04 | 1.21E+04 | 8.66E-01 | 1.50E+05 | 2.53E+02 | -5.34E+04 |
| | | | | CO2 | kg | 9.96E+02 | 1.22E+02 | 3.48E+01 | 1.83E+03 | 4.94E+01 | -1.06E+03 |
| Sox | kg | | | 7.38E-01 | 9.29E-02 | 1.93E-02 | 1.44E+00 | 3.40E-02 | -9.98E-01 | | |
| Nox | kg | | | 1.18E+00 | 7.56E-02 | 1.34E-01 | 2.33E+00 | 2.25E-01 | -1.70E+00 | | |
| N2O | kg | | | 8.11E-02 | 1.53E-03 | 6.28E-03 | 1.88E-01 | 2.97E-04 | -1.11E-01 | | |
| CH4 | kg | | | 8.59E-03 | 2.82E-03 | 2.07E-07 | 2.52E-02 | 5.48E-05 | -2.04E-03 | | |
| CO | kg | | | 1.58E-01 | 1.80E-02 | 2.88E-02 | 3.71E-01 | 7.32E-02 | -2.15E-01 | | |
| NMVOc | kg | | | 1.68E-02 | 5.53E-03 | 4.06E-07 | 4.93E-02 | 1.07E-04 | -4.00E-03 | | |
| CxHy | kg | | | 3.91E-02 | 3.94E-04 | 4.48E-03 | 5.92E-02 | 3.61E-03 | -5.27E-02 | | |
| Impact by Emission/Discharge to the environment | to Water system | Dust | kg | 1.36E-01 | 4.24E-03 | 1.35E-02 | 1.70E-01 | 1.42E-02 | -1.88E-01 | | |
| | | to Water domain | BOD | kg | - | 1.89E-02 | - | - | - | - | |
| | | | COD | kg | - | - | - | - | - | - | |
| | | N total | kg | - | - | - | - | - | - | | |
| | | P total | kg | - | - | - | - | - | - | | |
| | | SS | kg | - | - | - | - | - | - | | |
| | | to Soil system | Unspecified Solid Waste | kg | 7.47E+00 | 9.27E-03 | 0 | 7.61E+01 | 7.78E-04 | -1.51E+01 | |
| | | | Slag | kg | 3.79E+01 | 0 | 0 | 1.14E+01 | 0 | -4.88E+01 | |
| | | | Sludge | kg | 1.00E+01 | 0 | 0 | 2.19E+01 | 0 | -3.19E+01 | |
| | | | Low level radio-active waste | kg | 2.27E-03 | 7.37E-04 | 5.42E-08 | 6.63E-03 | 1.43E-05 | -6.09E-04 | |
| Impact assessment | to Global Warming | Energy resources (crude oil equivalent) | kg | 3.25E+02 | 4.59E+01 | 1.09E+01 | 7.16E+02 | 4.75E+00 | -3.26E+02 | | |
| | | Mineral resources (Iron ore equivalent) | kg | 1.52E+03 | 0 | 0 | 9.52E+02 | 0 | -3.48E+03 | | |
| | | Global Warming (CO2 equivalent) | kg | 1.02E+03 | 1.23E+02 | 3.65E+01 | 1.88E+03 | 4.94E+01 | -1.09E+03 | | |
| | | Acidification (SO2 equivalent) | kg | 1.56E+00 | 1.46E-01 | 1.13E-01 | 3.07E+00 | 1.91E-01 | -2.19E+00 | | |

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 - (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
 - Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
 - Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
 - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. We include package and attached articles, such as CD-ROM, operation manual in the product weight. Toner container as standard is included in the use stage, not in the product weight.
 2. Production stage: Environmental impacts on main product, toner supplied with and drum are included in this stage. Production of main product is included as China production. Toner and drum are included as Japan production.
 3. Transportation stage: Marine transport distance of a main product is 2,600km and domestic transport distance based on PCR provisions is 100km.
 4. Use stage: Based on PCR provision, impact on 2,066,700 sheets monochrome, 1,470,000 sheets color printing by user for five years is considered.
 5. Disposal/Recycle: We have calculated on the basis of a performance-based recycle scenario.
- This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Product data sheet

(Input data and parameters for LCA)



| | |
|--------------------------|---------------------------------|
| Document control no. | F-03s-02 |
| Product vendor | KYOCERA Document Solutions Inc. |
| EcoLeaf registration no. | AD-20-E1183 |

| | | | | | | | |
|-----------------------|----------------------------------|---------------------|-----------------|--------------|------|-------------------|-------|
| PCR name | EP and IJ Printer (PCR-ID:AD-04) | Product type | TASKalfa 8353ci | | | | |
| LCA/LCIA in units of: | 1 Unit | Product weight (kg) | 186.8 | Package (kg) | 38.3 | Weight total (kg) | 225.1 |

1. Product information (per unit): parts etc. by material and by process/assembly method

| Product | Breakdown of primary materials | | | | Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C) | | | |
|---------------------------|--------------------------------|------------------------------|---------------|-------------------------------------|--|-------------|---------------------|-------------|
| | Material name | Weight (kg) | Material name | Weight (kg) | Process name | Weight (kg) | Process name | Weight (kg) |
| | Carbon steel(kg) | 9.89E+01 | Rubber (kg) | 1.45E-01 | Press molding:Iron (kg) | 1.03E+02 | Parts assembly (kg) | 2.24E+02 |
| SUS (kg) | 3.89E+00 | Paper (kg) | 1.41E+01 | Press molding:Nonferrous metal (kg) | 7.43E+00 | | | |
| Cu (kg) | 3.70E+00 | Wood (kg) | 2.10E+01 | Injection molding (kg) | 6.02E+01 | | | |
| Al (kg) | 4.41E+00 | Assembled circuit board (kg) | 8.58E+00 | Blow molding (kg) | 3.89E-01 | | | |
| Other metals (kg) | 3.62E-02 | Medium-sized motor (kg) | 7.58E+00 | Glass molding (kg) | 2.19E+00 | | | |
| Glass (kg) | 2.19E+00 | | | | | | | |
| Thermoplastics resin (kg) | 5.97E+01 | | | | | | | |
| Thermosetting resin (kg) | 9.54E-01 | | | | | | | |
| Subtotal | 1.74E+02 | Subtotal | 5.14E+01 | | | | | |
| Total | | Subtotal | 2.25E+02 | Subtotal | 1.73E+02 | Subtotal | 2.24E+02 | |

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

| Consumption | Classification | Energy | Material | Energy | Energy | | | | |
|--------------------|----------------|-------------------|-----------------------|------------------------|-----------------------|--|--|--|--|
| | Distribution | Electricity (kWh) | Industrial water (kg) | Heavy oil as fuel (kg) | Gasoline as fuel (kg) | | | | |
| | Quantity | 3.71E+01 | 2.46E+02 | 3.12E-01 | 3.60E-03 | | | | |
| | Note | | | | | | | | |
| Emission/Discharge | Classification | Water system | | | | | | | |
| | Distribution | BOD | | | | | | | |
| | Quantity | 1.89E-02 | | | | | | | |
| | Note | | | | | | | | |

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

| Distribution | Means of transportation | Diesel truck:10 ton (kg·km) | Diesel truck:10 ton (kg·km) | Diesel truck:10 ton (kg·km) | Diesel truck:10 ton (kg·km) | Freight by ship (kg·km) | Freight by ship (kg·km) | Freight by ship (kg·km) | Freight by ship (kg·km) |
|--------------|-------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| | Conditions | Mass(kg) | Distance (km) | Loading Ratio(%w) | Load(kg·km) | Mass(kg) | Distance (km) | Loading Ratio(%w) | Load(kg·km) |
| | Quantity | 2.25E+02 | 1.00E+02 | 4.05E+01 | 5.56E+04 | 2.25E+02 | 2.60E+03 | 1.00E+02 | 5.85E+05 |
| | Note | | | | | | | | |

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

| Product | Classification | Process | Consumption | Consumption | Process | Process | Process | Process | Process |
|----------|----------------|---|--|---|--|---|--|----------------------------------|-------------------------------------|
| | Distribution | Diesel truck:2 ton (kg·km) | Electricity (kWh) | Industrial water (kg) | Injection molding (kg) | Blow molding (kg) | Parts assembly (kg) | Press molding:Iron (kg) | Press molding:Nonferrous metal (kg) |
| | Quantity | 7.78E+04 | 1.93E+03 | 2.40E+00 | 8.41E+01 | 8.65E-01 | 2.62E+02 | 3.12E+01 | 8.60E+00 |
| | Note | | | | | | | | |
| | Classification | Process <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption</td> </td></td></td></td></td></td> | Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption</td> </td></td></td></td></td> | Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption</td> </td></td></td></td> | Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption</td> </td></td></td> | Consumption <td>Consumption <td>Consumption <td>Consumption</td> </td></td> | Consumption <td>Consumption <td>Consumption</td> </td> | Consumption <td>Consumption</td> | Consumption |
| | Distribution | Glass molding (kg) | Carbon steel(kg) | SUS (kg) | Cu (kg) | Al (kg) | Other metals (kg) | Glass (kg) | Thermoplastics resin (kg) |
| | Quantity | 8.54E-02 | 3.01E+01 | 5.24E+00 | 4.62E-01 | 9.64E+00 | 1.09E-01 | 8.54E-02 | 2.08E+02 |
| | Note | | | | | | | | |
| | Classification | Consumption <td>Consumption <td>Consumption <td>Consumption <td>Consumption <td></td> <td></td> <td></td> </td></td></td></td> | Consumption <td>Consumption <td>Consumption <td>Consumption <td></td> <td></td> <td></td> </td></td></td> | Consumption <td>Consumption <td>Consumption <td></td> <td></td> <td></td> </td></td> | Consumption <td>Consumption <td></td> <td></td> <td></td> </td> | Consumption <td></td> <td></td> <td></td> | | | |
| | Distribution | Thermosetting resin (kg) | Rubber (kg) | Paper (kg) | Assembled circuit board (kg) | Medium-sized motor (kg) | | | |
| Quantity | 1.49E+00 | 2.86E-01 | 1.34E+02 | 1.16E+00 | 1.35E+00 | | | | |
| Note | | | | | | | | | |

Note

4.2 Disposition/Recycle information on consumables and replacement parts

| Consumables | Classification | Process | Process | Process | Process | Process | Process | Process | Deduction |
|-------------|----------------|---|--|---|--|---|--|------------------------------|------------------|
| | Distribution | Shredding (kg) | Recycle to copper plate (kg) | Recycle to Thermoplastic pellet (kg) | Recycle to corrugated cardboard (kg) | Recycle to cold-rolled steel (kg) | Recycle to Aluminum plate (kg) | Recycle to Glass (kg) | Carbon steel(kg) |
| | Quantity | 2.66E+02 | 2.97E+00 | 8.35E+01 | 1.34E+02 | 3.54E+01 | 9.64E+00 | 8.54E-02 | 3.01E+01 |
| | Note | | | | | | | | |
| | Classification | Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td> | Deduction <td>Deduction <td>Deduction</td> </td> | Deduction <td>Deduction</td> | Deduction |
| | Distribution | SUS (kg) | Cu (kg) | Al (kg) | Other metals (kg) | Glass (kg) | Thermoplastics resin (kg) | Paper (kg) | |
| Quantity | 5.24E+00 | 2.97E+00 | 9.64E+00 | 1.09E-01 | 8.54E-02 | 8.35E+01 | 1.34E+02 | | |
| Note | | | | | | | | | |

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

| Scenario | Classification | Process | Process | Process | Consumption | Process | Process | Process | |
|--------------|----------------|---|--|---|--|---|--|------------------------------|--------------------------------|
| | Distribution | Diesel truck:10 ton (kg·km) | Diesel truck:2 ton (kg·km) | Incineration: Industrial waste (kg) | Electricity (kWh) | Shredding (kg) | Recycle to cold-rolled steel (kg) | Recycle to copper plate (kg) | Recycle to Aluminum plate (kg) |
| | Quantity | 2.22E+04 | 5.78E+04 | 2.38E+01 | 6.60E-01 | 2.03E+02 | 1.03E+02 | 1.99E+01 | 4.41E+00 |
| | Note | | | | | | | | |
| | Classification | Process <td>Process <td>Process <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td></td></td> | Process <td>Process <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td></td> | Process <td>Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td></td> | Deduction <td>Deduction <td>Deduction <td>Deduction</td> </td></td> | Deduction <td>Deduction <td>Deduction</td> </td> | Deduction <td>Deduction</td> | Deduction |
| | Distribution | Recycle to Thermoplastic pellet (kg) | Recycle to corrugated cardboard (kg) | Recycle to Glass (kg) | Carbon steel(kg) | SUS (kg) | Cu (kg) | Al (kg) | Other metals (kg) |
| | Quantity | 5.97E+01 | 1.41E+01 | 2.19E+00 | 9.89E+01 | 3.89E+00 | 1.99E+01 | 4.41E+00 | 3.62E-02 |
| | Note | | | | | | | | |
| | Classification | Deduction <td>Deduction <td>Deduction <td></td> <td></td> <td></td> <td></td> <td></td> </td></td> | Deduction <td>Deduction <td></td> <td></td> <td></td> <td></td> <td></td> </td> | Deduction <td></td> <td></td> <td></td> <td></td> <td></td> | | | | | |
| Distribution | Glass (kg) | Thermoplastics resin (kg) | Paper (kg) | | | | | | |
| Quantity | 2.19E+00 | 5.97E+01 | 1.41E+01 | | | | | | |
| Note | | | | | | | | | |

Note

6. Others

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.