Product Environmental Aspects Declaration

EP and IJ printer (PCR number: AD-04)



No. AD-10-117 Date of publication Aug./31/2010



http://www.brother.co.jp/

For inquiry:

Product Environmental Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2735 FAX: +81-52-824-5667



Black & White Laser Printer HL-2270DW


Specifications:

- Electrophotographic Printer (EP)
- Black & White
- Printing Speed: 26ppm
- Maximum Printing Size: A4
- Flexible Wireless & Wired Interfaces
- Duplex Printing

The following data is calculated by assuming the product prints 405,600 sheets in 5-year usage period.

< Main environmental impact in the product lifecycle >

- Energy consumption
- 13,200MJ
- Global warming impact (CO2 equivalent)
- 760kg 1.26ka
- Acidification impact (SO2 equivalent)



- Electric power consumption in 5 years of "Use stage" is 318kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

[Supplemental environmental information]

The product assembly and main parts of toner and photoconductor are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program and the Law on Promoting Green Purchasing in Japan. The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Hisashi Ishitani, KEIO University Independent verification of the label and data, according to ISO 14025:2006 ☐ internal ■ external Third party verifier *: Kazuo Naitou

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

^{*} In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
Ecol eaf registration no.	AD-10-117

Unit Function DB version v2.1 Characterization Factor DB version v2.1

PCR name	EP and IJ print	Product type	HL-2270DW				
PCR code	AD-04	Product weight (kg)	6.9	Package (kg)	1.34	Weight total (kg)	8.24

				Life Cycle Stage		Produ	ıction	51 / 11 /		- ·	T
In/Out	t items				Unit	Raw material	Product	Distribution	Use	Disposal	Total
		Enoray	Cone	umption	MJ	1.01E+03	8.53E+01	1.91E+01	1.21E+04	7.69E+00	1.32E+04
				•	Mcal	2.41E+02	2.04E+01	4.57E+00	2.88E+03	1.84E+00	3.15E+03
			Energy resources	Coal	kg	5.14E+00	5.18E-01	4.47E-05	7.12E+01	4.63E-02	7.69E+01
			erg nrc	Crude oil (for fuel)	kg	1.03E+01	7.87E-01	4.18E-01	1.01E+02	8.20E-02	1.12E+02
			En	LNG	kg	2.21E+00	2.76E-01	6.45E-03	2.60E+01	2.38E-02	2.85E+01
		_	2	Uranium content of an ore	kg	2.15E-04	3.51E-05	3.03E-09	2.38E-03	3.13E-06	2.64E-03
				Crude oil (for material)	kg	4.06E+00	0	0	4.55E+01	0	4.95E+01
		(n		Iron content of an ore	kg	1.96E+00	0	0	3.17E+01	0	3.36E+01
		Exhaustible resources		Cu content of an ore	kg	1.34E-01	0	0	9.35E-03	0	1.43E-01
	Impact by Resource Consumption	ī		Al content of an ore	kg	1.77E-01	0	0	4.01E+00	0	4.19E+00
	act by Resou Consumption	res	S	Ni content of an ore	kg	6.60E-03	0	0	1.18E-01	0	1.25E-01
	tes	<u>0</u>	Mineral resources	Cr content of an ore	kg	9.51E-03	0	0	1.71E-01	0	1.80E-01
	y R	otip	oo	Mn content of an ore Pb content of an ore	kg kg	9.96E-03 6.69E-03	0	0	1.87E-01 7.60E-04	0	1.97E-01 7.45E-03
	t b	ans	ĕ	Sn content of an ore	kg kg	0.09E-03	-	-	7.00E-04	-	7.45E-03
	Cog	ı X	폡	Zn content of an ore	kg	6.59E-02	0	0	7.46E-03	0	7.34E-02
	Ē	ш	ie	Au content of an ore	kg	0.39E-02	-	-	7.40E-03	-	7.34E-02
			Σ	Ag content of an ore	kg	-	-	-	-	-	
				Silica Sand	kg	2.25E-01	0	0	3.74E-01	0	5.99E-01
S				Halite	kg	2.19E+00	9.82E-05	0	3.58E+00	2.46E-03	5.78E+00
Š				Limestone	kg	5.56E-01	6.36E-03	0	7.66E+00	6.40E-02	8.29E+00
aj.				Natural soda ash	kg	2.05E-02	0.302-03	0	0	0.402-02	2.05E-02
Inventory anaiyses		Renew	vable	Wood	kg	2.22E+00	2.09E-01	0	8.47E+01	0	8.71E+01
		resou		Water	kg	5.38E+03	4.05E+02	3.38E-02	4.29E+04	3.92E+01	4.87E+04
윧				CO2	kg	5.22E+01	4.86E+00	1.36E+00	6.82E+02	6.90E+00	7.47E+02
Ş				SOx	kg	3.67E-02	3.39E-03	8.31E-04	5.11E-01	3.62E-03	5.55E-01
⊆				NOx	kg	6.86E-02	4.19E-03	6.55E-03	9.13E-01	7.73E-03	1.00E+00
	Φ to			N2O	kg	4.82E-03	2.00E-04	2.27E-04	4.24E-02	1.02E-05	4.77E-02
				CH4	kg	5.72E-04	9.38E-05	8.09E-09	6.30E-03	8.38E-06	6.97E-03
	Emission/Discharge e environment	Atmosp	onere	CO	kg	7.10E-03	6.97E-04	1.72E-03	1.45E-01	1.42E-03	1.56E-01
	ch t			NMVOC	kg	1.12E-03	1.84E-04	1.58E-08	1.23E-02	1.64E-05	1.37E-02
	Dis			СхНу	kg	2.25E-03	7.36E-05	1.95E-04	2.04E-02	2.69E-05	2.30E-02
	l/uc			Dust	kg	7.10E-03	2.77E-04	6.24E-04	7.84E-02	4.41E-04	8.68E-02
	ssic			BOD	kg	-	-	-	-	-	
	mis	to		COD	kg	-	-	-	-	-	
	/ E	Water d		N total	kg	-	-	-	-	-	
	t by Emission/Disc to the environment	vvaler d	omain	P total	kg	-	•	-		-	
	ac			SS	kg	-	•	-	i	-	
	Impact by to th			Unspecified Solid Waste	kg	4.67E-01	2.63E-03	0	5.32E+01	3.08E+00	5.68E+01
				Slag	kg	7.30E-01	0	0	9.67E+00	0	1.04E+01
		to		Sludge	kg	3.32E-01	0	0	8.61E+00	0	8.94E+00
		Soil sy	stem	Low level radio-active waste	kg	1.51E-04	2.45E-05	2.12E-09	1.66E-03	2.19E-06	1.84E-03
Ħ	source	Exhau	stible	Energy resources (crude oil equivalent)	kg	1.80E+01	1.74E+00	4.26E-01	1.97E+02	1.66E-01	2.18E+02
essme	by Resource Consumption	resou	rces	Mineral resources (Iron ore equivalent)	kg	4.06E+01	0	0	1.66E+02	0	2.07E+02
Impact assessment	≾ by Discharg	to		Global Warming (CO2 equivalent)	kg	5.35E+01	4.91E+00	1.42E+00	6.94E+02	6.90E+00	7.60E+02
dwl	Impact by Emission/Discharg e	Atmosp		Acidification (SO2 equivalent)	kg	8.47E-02	6.33E-03	5.41E-03	1.15E+00	9.03E-03	1.26E+00

[Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below.

- (1) "Raw material" production: consists of mining, transportation and raw material production.
 (2) "Product" production: consists of the parts processing, assembly and installation.

 B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal.

- II. Inventory analyses

 A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV. Data entry format

- A. Exponential notation, after the decimal point to two, should be used.

 B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

 C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- 1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance
- The transportation distance in Japan uses 100 km as average distance
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 405600 sheets, calculated by supposing a user use a machine for 5 years.

 It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure.
- The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.
- The distribution impact of consumables is calculated under the same condition of products:
- The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance
- Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.
- 5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material
- This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

Product data sheet

Input data and parameters for LCA

	(input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AD-10-117



PSC name	EP and IJ printer(PCR ID:AD-04)	Product type	HL-2270DW					
LCA/LCIA in units of:	1	Product weight (kg)	6.9	Package (kg)	1.34	weight total (kg)	8.24	

1. Product information (per unit): parts etc. by material and by process/assembly method

		Breakdown of pri	mary materials		Math breakdown of parts, which need to apply Processing / Assembly base Units (Parts B,C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
	Steel	1.61E+00	Paper	1.04E+00	Press molding: Iron (kg)	1.65E+00	Parts assembly (kg)	1.41E+00	
#	Stainless steel	4.15E-02	Semiconductor substrate	5.95E-01	Press molding: Nonferrous metal (kg)	1.03E-01			
声	Aluminum	1.46E-01	Wood	3.30E-04	injection molding (kg)	4.46E+00			
Ιĕ	Other metal	9.40E-04	Medium-sized motor	2.59E-01	Glass molding (kg)	6.89E-02			
_	Thermoplastic resin	4.35E+00	Batteries	0.00E+00					
	Thermosetting resin	2.00E-05	Lubricants	1.15E-03					
	Rubber	1.37E-01	Clean water	0.00E+00					
	Glass	6.89E-02							
	Subtotal	6.35E+00	Subtotal	1.89E+00					
		Total		8.24E+00	Subtotal	6.28E+00	Subtotal	1.41E+00	
Nista		Total		0.242100	Gubtotai	0.202100	Cubiciai	1.412100	

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO_2 , NO_2 equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Energy
Ē	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Diesel truck: 2 ton (kg.km)	Incineration: Industrial waste (kg)	LNG as fuel (kg)	Gasoline as fuel (kg)	Freight by ship (kg.km)
tio	Quantity	9.82E-02	2.19E+00	2.04E+01	2.55E+01	9.82E-02	1.36E-02	1.20E-05	7.74E+01
d L	Note								
Ins	Classification	Energy	Energy						
Con	Distribution	Kerosene as fuel (kg)	Heavy oil fuel (kg)						
	Quantity	4.02E-06	1.50E-01						
	Note								
-/ e	Classification								
Emission Discharge	Distribution								
is is	Quantity								
шО	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)			
_	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
ō	Quantity	8.24E+00	3.00E+01	2.95E+01	8.37E+02	8.24E+00	2.54E+03	1.00E+02	2.09E+04
Ĭ	Note								
ŧ	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:				
is	transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)				
_	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	8.24E+00	1.00E+02	2.95E+01	2.79E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck:	Freight by	Diesel truck:	Electroplated steel	Stainless steel	Aluminum	Copper
	Distribution	Liectricity (KWII)	20 ton (kg.km)	ship (kg.km)	10 ton (kg.km)	Plate (kg)	plate (kg)	plate (kg)	plate (kg)
	Quantity	3.18E+02	1.65E+04	3.10E+05	5.49E+04	3.03E+01	7.43E-01	3.80E+00	3.10E-02
		Electricity	Distribution of	Distribution of	Distribution of				
	Note	consumption for		consumables used in					
		5 years	5 years	5 years	5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Low density	PP (kg)	PS (kg)	Polycarbonate	POM(polyacetal)	ABS (kg)	AS resin (kg)	PET (kg)
	Distribution	polyethylene (kg)	ii (kg)	1 5 (kg)	(kg)	(kg)	ADO (kg)	Ao resiir (kg)	TET (kg)
[Quantity	6.98E-01	8.00E-01	2.37E+01	1.39E+00	3.91E+00	3.01E+00	8.45E+00	3.83E-01
헐	Note								
5	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
ď	Distribution	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	injection molding (kg)	Press molding: Iron (kg)	Press molding: Nonferrous metal (kg)
	Quantity	5.93E-01	5.83E+00	2.32E+01	1.37E+01	1.76E+00	4.03E+01	3.10E+01	2.37E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption		
	Distribution	Parts assembly	Gasoline as	Kerosene as	Heavy oil	LNG as	Electricity (kwh)		
	Distribution	(kg)	fuel (kg)	fuel (kg)	fuel (kg)	fuel (kg)	Electricity (kwri)		
	Quantity	2.48E+01	4.76E-04	1.58E-04	5.85E+00	4.49E-01	1.01E+02		
			Production of	Production of	Production of	Production of	Production of		
	Note				consumables used in	consumables used in			
			5 years	5 years	5 years	5 years	5 years		

Note $\,$ At "Use Stage", the product electricity consumption in 5 years usage period is 318 kWh .

4.2 Disposition/Recycle information on consumables and replacement parts

4.2 DIS	z disposition/Recycle information on consumables and replacement parts												
Se	Classification	Consumption	Process	Process	Process								
nable	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)								
uns	Quantity	7.38E+03	7.63E+01	7.99E+01	3.53E+01								
Cons	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected								
Note													

5. Disposition/Recycle stage information (per product): process method and scenarios

	Classification	Consumption	Process	Process	Process		
ario	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)		
Ser	Quantity	7.11E+02	6.00E+00	5.04E+00	2.30E+00		
Sc	Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected		