Product Environmental Aspects Declaration

EP and IJ printer (PCR number: AD-04)



No. AD-11-149 Date of publication May/17/2011



http://www.brother.co.jp/

For inquiry:

Product Environmental Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2735 FAX: +81-52-824-5667


Laser Multi-Function Center DCP-7065DN Specifications:

- · Electrophotographic Printer (EP)
- · Black & White
- Printing Speed: 26 ppm Maximum Printing Size: A4
- Duplex Printing

The following data is calculated by assuming the product prints 405,600 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 14,000MJ
- Global warming impact (CO₂ equivalent) 804kg
- Acidification impact (SO₂ equivalent) 1.32kg





- Electric power consumption in 5 years of "Use stage" is 299kWh.
- · The above data does not include the environmental impact of the paper that is used for printing.

Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

[Supplemental environmental information]

The product assembly and main parts of toner and photoconductor are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, February 01, 2011, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

^{*} In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)

Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AD-11-149



Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	EP and IJ print	ter	Product type	DCP-7065DN			
PCR code	AD-04	Product weight (kg)	11.4	Package (kg)	2.76	Weight total (kg)	14.1

Life Cycle Stage		Life Cycle Stage	Unit	Produ	ction	Distribution	Use	Dienocal	Total		
In/Out	titems					Raw material	Product	Distribution	USE	Disposal	Total
		Energ	v Cons	umption	MJ	1.53E+03	1.41E+02	5.00E+01	1.23E+04	1.41E+01	1.40E+04
		Lileig		•	Mcal	3.66E+02	3.36E+01	1.19E+01	2.93E+03	3.36E+00	3.35E+03
			Energy resources	Coal	kg	7.15E+00	9.09E-01	1.17E-04	7.31E+01	8.51E-02	8.13E+01
			Energy	Crude oil (for fuel)	kg	1.59E+01	1.14E+00	1.09E+00	9.96E+01	1.50E-01	1.18E+02
			Sol	LNG	kg	3.08E+00	4.71E-01	1.69E-02	2.70E+01	4.38E-02	3.06E+01
			I Fe	Uranium content of an ore	kg	3.07E-04	6.15E-05	7.92E-09	2.52E-03	5.75E-06	2.89E-03
				Crude oil (for material)	kg	6.84E+00	1.12E-02	0	4.57E+01	0	5.25E+01
				Iron content of an ore	kg	2.74E+00	0	0	3.17E+01	0	3.44E+01
		sec		Cu content of an ore	kg	1.75E-01	0	0	9.35E-03	0	1.84E-01
	e	ını		Al content of an ore	kg	1.84E-01	0	0	4.01E+00	0	4.20E+00
	Impact by Resource Consumption	sso	m	Ni content of an ore	kg	9.38E-03	0	0	1.18E-01	0	1.27E-01
	oact by Resou Consumption	9 F6	Exhaustible res	Cr content of an ore	kg	1.35E-02	0	0	1.71E-01	0	1.84E-01
	8 E	Exhaustible resources		Mn content of an ore	kg	1.41E-02	0	0	1.87E-01	0	2.01E-01
	by Isu		esc	Pb content of an ore	kg	8.80E-03	0	0	7.60E-04	0	9.56E-03
	o gc		hat al re	Sn content of an ore	kg	-	-	-	ı	-	
	<u>ğ</u> 0	Ä	era	Zn content of an ore	kg	8.67E-02	0	0	7.46E-03	0	9.42E-02
	드		i	Au content of an ore	kg	-	-	-		-	
			_	Ag content of an ore	kg	-	-	-	-	-	
				Silica Sand	kg	7.55E-01	0	0	3.74E-01	0	1.13E+00
S				Halite	kg	4.61E+00	1.10E-04	0	3.59E+00	4.27E-03	8.20E+00
\Se				Limestone	kg	9.14E-01	7.10E-03	0	7.90E+00	1.19E-01	8.94E+00
jaj.				Natural soda ash	kg	7.93E-02	0	0	0	0	7.93E-02
Inventory anaiyses		Rene	wable	Wood	kg	4.63E+00	2.09E-01	0	9.21E+01	0	9.69E+01
È		resou	urces	Water	kg	7.36E+03	7.02E+02	8.84E-02	4.49E+04	7.21E+01	5.30E+04
뒫				CO2	kg	7.75E+01	7.57E+00	3.55E+00	6.90E+02	1.28E+01	7.92E+02
\ \				SOx	kg	5.10E-02	5.54E-03	2.07E-03	5.19E-01	6.71E-03	5.84E-01
⊆		±		NOx	kg	1.04E-01	5.10E-03	1.53E-02	9.08E-01	1.43E-02	1.05E+00
				N2O	kg	7.46E-03	1.41E-04	6.18E-04	3.80E-02	1.85E-05	4.62E-02
	Φ	t t		CH4	kg	8.18E-04	1.65E-04	2.12E-08	6.65E-03	1.54E-05	7.65E-03
	arg	Atmosphe e environment to to		CO	kg	9.90E-03	1.13E-03	3.68E-03	1.49E-01	2.60E-03	1.66E-01
	t cha			NMVOC	kg	1.60E-03	3.22E-04	4.14E-08	1.30E-02	3.02E-05	1.50E-02
)isi	to Water domain		СхНу	kg	3.50E-03	4.14E-05	4.83E-04	1.88E-02	4.84E-05	2.29E-02
	7 2			Dust	kg	1.07E-02	2.52E-04	1.50E-03	7.51E-02	8.12E-04	8.83E-02
	sio			BOD	kg	-	-	-	-	-	0.002 02
	nis V			COD	kg	-	-	_	-	-	
	En e e	te		N total	kg	-	-	-	-	-	
	β₽	Water	domain	P total	kg	-	-	_	-	-	
	to to			SS	kg	-		-	_		
	Impact by to th			Unspecified Solid Waste	kg	7.09E-01	2.98E-03	0	5.33E+01	5.34E+00	5.94E+01
	≟			Slag	kg	1.01E+00	0	0	9.67E+00	0	1.07E+01
		te	0	Sludge	kg	3.31E-01	0	0	8.61E+00	0	8.94E+00
		Soil s			ĸg	3.31L-01	0	0	0.012+00	0	0.342+00
		000	, 0.0	Low level	kg	2.15E-04	4.30E-05	5.53E-09	1.76E-03	4.02E-06	2.02E-03
				radio-active waste	ĸg	2.131-04	4.50L-05	3.33L-03	1.702-03	4.02L-00	2.02L-03
				Energy resources							
	tion			(crude oil equivalent)	kg	2.67E+01	2.79E+00	1.11E+00	2.00E+02	3.04E-01	2.31E+02
	by Resource Consumption	Exhau		(crude oil equivalent)							
	Re	resou	urces	Mineral resources							
t en	े ह			(Iron ore equivalent)	kg	5.47E+01	6.19E-03	0	1.66E+02	0	2.21E+02
Impact assessment				,							
ημ	Impact by Emission/Discharge to the environment			Global Warming		7.055	7015	0.707	7015	4.00=	0.045
= ass	cha			(CO2 equivalent)	kg	7.95E+01	7.61E+00	3.72E+00	7.01E+02	1.28E+01	8.04E+02
a	Dis Viro	to		(
	Impact by sion/Disch e environr	Atmos	phere	Acidification							
	l ssr			Acidification (SO2 equivalent)	kg	1.24E-01	9.11E-03	1.28E-02	1.15E+00	1.67E-02	1.32E+00
	- H			(302 equivalent)							

[Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
 (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage. C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).

 D. "Disposal" stage in intended for environmental impacts by product disposal.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.

 B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV. Data entry format

- A. Exponential notation, after the decimal point to two, should be used.

 B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

 C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- 1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 405600 sheets, calculated by supposing a user use a machine for 5 years

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.

Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

Product data sheet (Input data and parameters for LCA)

	(input data and parameters for 2011)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AD-11-149



PSC name	EP and IJ printer(PCR ID:AD-04)	Product type	DCP-7065DN					
LCA/LCIA in units of:	1	Product weight (kg)	11.4	Package (kg)	2.76	weight total	14.1	

1. Product information (per unit): parts etc. by material and by process/assembly method

		Breakdown of pr	imary materials			Math breakd			
		<u> </u>	<u> </u>		which need to apply Processing / Assembly base Units (Parts B,C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
	Steel	2.27E+00	Paper	2.16E+00	Press molding: Iron (kg)	2.33E+00	Parts assembly (kg)	2.03E+00	
支	Stainless steel	Stainless steel 5.90E-02 Semiconductor substrate 7.84E-01 Press molding: Nonferrous metal (kg) 1.03E-01							
ΙΞ	Aluminum	1.46E-01	Wood	0	Injection molding (kg)	7.63E+00			
ĕ	Other metal	9.40E-04	Medium-sized motor	3.35E-01	Glass molding (kg)	7.14E-01			
<u> </u>	Thermoplastic resin	7.39E+00	Lubricants	7.77E-04					
	Thermosetting resin	5.20E-02							
	Rubber	2.07E-01							
	Glass	7.14E-01							
	Subtotal	1.08E+01	Subtotal	3.28E+00					
		Total		1.41E+01	Subtotal	1.08E+01	Subtotal	2.03E+00	
Make	<u> </u>	-	<u> </u>	•	•				

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site. ${\rm SOx}$ and ${\rm NOx}$ should be indicated in ${\rm SO}_2,$ ${\rm NO}_2$ equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Energy
Ē	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 10 ton (kg.km)	Diesel truck: 2 ton (kg.km)	Incineration: Industrial waste (kg)	LNG (kg)	Diesel oil as fuel (kg)	Freight by ship (kg.km)
l ≅	Quantity	9.82E-02	4.98E+00	1.82E+01	2.53E+01	1.10E-01	1.36E-02	2.47E-02	2.88E+02
mption	Note								
ınsıı	Classification	Material	Energy	Energy	Energy				
Co	Distribution	PP (kg)	Heavy oil fuel (kg)	Diesel truck: 20 ton (kg.km)	LPG(NPG) as fuel (kg)				
	Quantity	1.13E-02	1.52E-03	1.52E+01	2.45E-02				
	Note								
- e	Classification								
ssion	Distribution								
Emis	Quantity								
	Note								

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)			
_	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
٥	Quantity	1.41E+01	5.00E+01	2.73E+01	2.59E+03	1.41E+01	4.06E+03	1.00E+02	5.74E+04
Ιž	Note								
istri	Means of transportation	Diesel truck: 10 ton (kg.km)							
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	1.41E+01	1.00E+02	2.71E+01	5.21E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

	-		•			,
4.1 P	roduct	and	accessories	subject to	this a	analysis

	aast ana ass	essories subject to	uno unuiyoio						
	Classification	Consumption	Consumption	Consumption	Consumption		Consumption	Consumption	Consumption
	Distribution	Diesel truck:	Freight by	Diesel truck:	Diesel truck:		Electroplated	Stainless	Copper
	Distribution	20 ton (kg.km)	ship (kg.km)	10 ton (kg.km)	2 ton (kg.km)		steel Plate (kg)	steel plate (kg)	plate (kg)
	Quantity	1.71E+04	3.21E+05	5.69E+04	1.67E+03		3.03E+01	7.43E-01	3.10E-02
		Distribution of	Distribution of	Distribution of	Distribution of				
	Note	consumables used in	consumables used in	consumables used in					
		5 years	5 years	5 years	consumables used in				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Aluminum plate (kg)	PP (kg)	Low density polyethylene (kg)	PS (kg)	Polycarbonate (kg)	POM(polyacetal) (kg)	ABS (kg)	AS resin (kg)
	Quantity	3.80E+00	9.69E-01	6.98E-01	2.37E+01	1.39E+00	3.91E+00	3.01E+00	8.45E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	PET (kg)	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	Injection molding (kg)	Press molding: Iron (kg)
ုင္	Quantity	3.83E-01	5.93E-01	5.83E+00	2.66E+01	1.37E+01	1.76E+00	4.03E+01	3.10E+01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Nonferrous metal	Parts assembly (kg)	Electricity (kwh)	Gasoline as fuel (kg)	Kerosene as fuel (kg)	Heavy oil fuel (kg)	LNG (kg)	Electricity (kwh)
	Quantity	2.37E+00	2.48E+01	2.99E+02	8.82E-05	8.37E-03	5.98E-01	4.49E-01	1.53E+02
				Electricity	Production of	Production of	Production of	Production of	Production of
	Note			consumption for		consumables used in			
				5 years	5 years	5 years	5 years	5 years	5 years
	Classification	Process							
	Distribution	Incineration: Industrial waste (kg)							
	Quantity	3.65E+00							
	Note	Packaging materials for distribution of ingredient							

Note 1. Electric power consumption in 5 years of "Use stage" is 299kWh.

2. Production of consumables by China.

- DIS	Disposition/recoyole information on consumatics and replacement parts													
S	Classification	Consumption	Process	Process	Process									
nable	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)									
l s	Quantity	7.02E+03	7.26E+01	7.96E+01	3.53E+01									
Son	Note	Consumables not collected												

5. Disposition/Recycle stage information (per product): process method and scenarios

Proposition of the stage in the matter (per product) processe method and obstante									
Scenario	Classification	Consumption	Process	Process	Process				
	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)				
	Quantity	1.28E+03	1.05E+01	9.35E+00	3.89E+00				
	Note	Machines not collected							

Note