Product Environmental Aspects Declaration



EP and IJ printer (PCR-ID:AD-04)

No. AD-12-187 Date of publication Jul./24/2012



http://konicaminolta.jp

Please direct any inquiries or comments to e-mail: bt-environ@pub.konicaminolta.jp



Marking technologies Electrophotographic Printer (EP)

Printing speed 125 prints-per-minute(B/W)

Maximum copy paper A3

<u>Duplex copying</u> Non-stack ADU equipped

Document feeding ADF with Auto-document reversing function equipped

Life Cycle Impact

Life Oyole impact	
Consumption and discharge in a life cycle	All the stage sum totals
Global warming(CO2equivalent):kg	5,569 (5,003)
Acidification(SO2equivalent):kg	7.9 (6.9)
Energy resources(crude oil equivalent):MJ	106,837 (97,888)


**Figures in() indicated environmental impact including recycle effect *note3

Warming load CO₂ equivalent of each stage(kg)



Total of 9,375,000 sheets on the assumption of five years usage.

Environmental impact by copypaper is not included.



Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Recycle Effect illustrates an indirect influence to other products/services.
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.

[Supplemental environmental information]



- Certified Environmental Standards
 - Japan Eco Mark
 - International Energy Star Program
- Conforming to Japanese Law on Promoting Green Purchasing

PCR review was conducted by: PCR Deliberation Committee, January 01,2008, Name of reprentative: Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025 □internal ■external Third party verifier*: Shozo Nakamuta

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)

Document control no.	F-02B-03	Unit Function DB version	v2.1
Product vendor	KONICA MINOLTA, INC.	Characterization Factor DB version	v2.1
EcoLeaf registration no.	AD-12-187	1	



DOD ED III						bizhub PRESS1250P					
	R nar		EP and IJ print	er	Product type						
PC	CR-I	D	AD-04		Product weight[kg]	345.0	Package[kg]	42.5	Weight total[kg]	387.5	
		_	Life Cycle Stage		Produ	ıction					
Out ite	ms			Unit	Raw material	Product	Distribution	Use	Disposal	Recycle	
	_			MJ	2.35E+04	4.96E+03	9.04E+02	7.72E+04	2.29E+02	-8.95E+03	
	Eı	nergy C	onsumption	Mcal	5.61E+03	1.19E+03	2.16E+02	1.84E+04	5.46E+01	-2.14E+03	
			Coal	kg	3.32E+02	3.20E+01	2.11E-03	4.62E+02	1.03E+00	-1.40E+02	
			Crude oil (as a fuel)	kg	1.80E+02	4.00E+01	1.98E+01	5.14E+02	2.59E+00	-5.28E+01	
		Energy	Natural Gas	kg	4.27E+01	1.62E+01	3.05E-01	2.11E+02	5.41E-01	-1.29E+01	
			Uranium ore	mg	4.58E-03	2.16E-03	1.43E-07	2.65E-02	6.99E-05	-6.27E-04	
			crude on (as an ingredients)	kg	2.55E+01	0	0	6.18E+01	0	-2.88E+01	
			Iron ore	kg	3.07E+02	0	0	2.33E+01	0	-1.32E+02	
			Copper ore	kg	5.20E+00	0	0	2.71E-03	0	-1.61E+00	
			Bauxite	kg	3.33E+00	0	0	1.97E+01	0	-9.21E+00	
5 ±			Nickel ore	kg	2.40E+00	0	0	8.86E-01	0	-1.32E+00	
mptik	stible	esonices	Chromium ore	kg	3.35E+00	0	0	1.21E+00	0	-1.82E+00	
onsu	Exhaustible resources		Manganese ore	kg	1.94E+00	0	0	2.66E-01	0	-2.74E-01	
Resource Consumption from the environment		Motorial	Plumbous ore	kg	2.26E-01	0	0	0	0	-5.43E-02	
soure		Material	Tin ore	kg	0	0	0	0	0	0	
Rei			Zinc ore	kg	2.22E+00	0	0	0	0	-5.34E-01	
			Gold ore	kg	0	0	0	0	0	0	
			Silver ore	kg	0	0	0	0	0	0	
			Silica sand	kg	6.93E+00	0	0	4.84E-01	0	-1.39E+00	
			Rock salt	kg	1.61E+01	3.94E-03	0	4.94E+00	1.56E-01	-7.00E+00	
0			Limestone	kg	6.21E+01	0	0	5.62E+00	7.27E-01	-2.17E+01	
lany			Natural soda ash	kg	3.04E-01	0	0	2.52E-02	0	-5.14E-02	
	Renew	/able	Wood	kg	6.33E+01	0	0	5.64E+01	0	-4.79E+01	
,	resour	ces	Water	kg	1.10E+05	2.89E+04	1.59E+00	3.40E+05	8.18E+02	-3.33E+04	
			CO2	kg	1.57E+03	2.61E+02	6.42E+01	3.55E+03	6.71E+01	-5.56E+02	
			SOx	kg	9.62E-01	1.95E-01	3.92E-02	3.24E+00	3.84E-02	-5.62E-01	
			NOx	kg	1.42E+00	1.78E-01	3.06E-01	2.89E+00	1.20E-01	-6.62E-01	
			N2O	kg	8.90E-02	5.61E-03	1.07E-02	9.25E-02	2.32E-04	-3.91E-02	
	to Atm	osphere	CH4	kg	1.22E-02	5.78E-03	3.83E-07	7.05E-02	1.87E-04	-1.51E-03	
			CO	kg	2.44E-01	3.78E-02	8.07E-02	6.47E-01	3.20E-02	-1.36E-01	
			NMVOC	kg	2.38E-02	1.13E-02	7.50E-07	1.38E-01	3.66E-04	-2.94E-03	
arge			СхНу	kg	4.70E-02	1.95E-03	9.21E-03	3.16E-02	1.23E-03	-1.97E-02	
nission/Discharge			dust	kg	1.89E-01	1.14E-02	2.94E-02	2.07E-01	7.49E-03	−9.13E−02	
ion/E			BOD	kg	-	-	-	-	-	-	
Emissi to the			COD	kg	-	ı	-	ı	-	ı	
ω×	to Wat	er system	N total	kg	-	ı	-	1	_	ı	
			P total	kg	-	-	_	_	_	-	
			SS	kg	_	-	-	_	_	-	
			Unspecified solid waste	kg	5.21E+00	6.83E-02	0	4.39E+01	1.92E+02	-4.48E+00	
	to Coil	system	Slag	kg	9.76E+01	0	0	7.63E+00	0	-3.93E+01	
	10 3011	system	Sludge	kg	4.83E+00	0	0	4.23E+01	0	-1.89E+01	
			Low emission radioactive waste	kg	3.20E-03	1.51E-03	1.00E-07	1.85E-02	4.88E-05	-4.39E-04	
o F			Energy resources (crude oil equivalent)	kg	4.82E+02	9.77E+01	2.01E+01	1.28E+03	4.48E+00	-1.63E+02	
by Resource Consumption	Exha	austible ources	Mineral resources	kg	3.37E+03	0	0	8.04E+02	0	-1.52E+03	
Con			(Iron ore equivalent)								
4336			Global warming (CO2 equivalent)	kg	1.59E+03	2.63E+02	6.71E+01	3.58E+03	6.71E+01	-5.67E+02	
by Emision by Res	Atmo	to osphere	(CO2 equivalent) Acidification (SO2 equivalent)	kg	1.96E+00	3.20E-01	2.54E-01	5.26E+00	1.22E-01	-1.03E+00	
En	to	Water									
3 2	şx	stem									
- 0											

[Notes for readers: EcoLeaf common rules]

- Production" stage is intended for two sub-stages listed below.
 (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.

 B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts)
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.

 B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body B. " Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding).
- C. Regarding the basis and the basic units for calculations during distribution stages
- D. Regarding the basis and the basic units for calculations during use and consumption stage
 E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04).
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Product data sheet

	(input data and parameters for L	
Document control no.	F-03-03	I
Product vendor	KONICA MINOLTA, INC.	7
EcoLeaf registration no.	AD-12-187	1



PCR name	EP and IJ printer(PCR-ID:A	Product type	bizhub PRESS1250P				
LCA/LCIA in units of:	1	Product weight[kg	345.0	Package[kg]	42.5	Weight total[kg]	387.5

1. Product information (per unit): parts etc. by material and by process/assembly method

	Breakdown	of primary materials	Math breakdown of par	ts, which need to apply	Processing / Assembly	Base Units (Parts B, C)	
Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel	2.90E+02	Semiconductor circuit board	1.23E+01	Press molding:Iron	2.93E+02	Parts assembly	6.35E-01
Stainless steel	1.52E+01			Press molding:Nonf errous metal	5.75E+00		
Aluminium	2.13E+00			Injection molding	2.18E+01		
Other metals	3.62E+00			Blow molding	3.73E-01		
Thermoplastic resin	2.44E+01						
Wood	1.51E+01						
Paper	2.26E+01						
Rubber	1.78E+00						
Subtotal	3.75E+02	Subtotal	1.23E+01				
	Total		3.88E+02	Subtotal	3.20E+02	Subtotal	6.35E-01

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

30x a	SOX and NOX should be indicated in SOZ, NOZ equivalent.											
5	Classification	Energy	Energy	Energy	Energy	Material	Material					
mption	Distribution	Electricity	Heavy oil as	Diesel oil as	Furnace urban	urban	Groundwater					
	Distribution	(kWh)	fuel(kg)	fuel(kg)	gas (m3)	water(kg)	(kg)					
Consu	Quantity	1.99E+02	3.70E+00	1.07E-01	1.20E-01	4.16E+03	3.62E+02					
0	Note											
	Classification To	To Water										
on ige		system										
Emission/ Discharge	Distribution	Sewage (kg)										
Emission/ Discharge	Quantity	6.80E+02										
	Note											

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

		Means of transportation	Freight by	Diesel truck	Diesel truck			
tjo	tion		ship	:20ton	:2ton			
	Distribu	Conditions	Load(kg·km)	Load(kg•km)	Load(kg•km)			
		Quantity	9.92E+05	1.99E+05	1.50E+03			
		Note						

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	Electricity (kWh)	Heavy oil as fuel(kg)	Diesel oil as fuel(kg)	Gasoline as fuel(kg)	Furnace urban gas (m3)	Groundwater (kg)	Ordinary steel (kg)	Stainless steel (kg)
_	Quantity	6.97E+03	6.51E-01	1.88E-02	9.35E-01	3.39E-01	1.95E+03	2.07E+01	5.61E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Processing	Processing
Product	Distribution	Aluminium (kg)	Copper(kg)	Glass (kg)	Thermoplastic resin(kg)	Paper(kg)	Rubber(kg)	Press:Iron (kg)	Press: Nonferrous(kg)
Δ.	Quantity	1.87E+01	9.00E-03	3.00E-01	5.20E+01	2.65E+01	1.11E+01	2.02E+01	5.21E+00
	Note								
	Classification	Processing	Processing	Processing	Assembly	To Water system	Distribution		
Product	Distribution	Injection molding(kg)	Blow molding(kg)	Glass molding(kg)	Parts assembly (kg)	Sewage (kg)	Diesel truck: 10ton (kg•km)		
	Quantity	4.02E+01	5.65E+01	3.00E-01	5.65E+01	1.75E+02	1.48E+04		
	Note								
	Classification								
Product	Distribution								
	Quantity								
	Note								

Classification Distribution	Consumption	Consumption	Treatment	Treatment	Treatment			
Distribution	Electricity.			Houtmont	rreatment	Treatment	Treatment	Treatment
	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
Quantity	3.69E+00	4.80E-02	1.05E+01	7.46E+00	3.60E-03	1.20E-01	2.06E+01	1.06E+01
Note								
Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
Distribution	Industrial waste destruction by fire(kg)	Industrial waste inning(kg)	Waste destruction by fire(kg)	Waste inning(kg)	Iron(kg)	Aluminum(kg)	Copper(kg)	Glass(kg)
Quantity	4.45E+00	2.08E-01	5.38E+01	2.71E+01	-1.05E+01	-7.46E+00	-3.60E-03	-1.20E-01
Note								
Classification	Deduction	Deduction	Distribution	Distribution				
Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
Quantity	-2.06E+01	-1.06E+01	6.47E+03	7.83E+03				
Note								
	Note Classification Distribution Quantity Note Classification Distribution Quantity Quantity Output Distribution	Note Classification Treatment Distribution Distribution Quantity Note Classification Distribution Distribution Distribution Plastics(kg) Quantity -2.06E+01	Note Classification Distribution Classification Distribution Distribution Classification Distribution Classification Deduction Distribution Distribution Distribution Deduction Deduction Deduction Distribution Deduction Deduction Deduction Deduction Distribution Deduction Deduction Distribution Deduction Deduction Distribution Deduction Deduction Deduction Distribution Deduction Deduction Distribution Deduction Deduction Deduction Distribution Deduction Deduction Deduction Deduction Distribution Distribution Deduction Deduction Distribution Deduction Deduction Deduction	Note Classification Distribution Distribut	Note Classification Treatment Trea	Note Classification Treatment Deduction	Note Classification Treatment Trea	Note Classification Treatment Deduction Description Distribution Di

5. Disposition/Recycle stage information (per product): process method and scenarios

_	Oberition in			•			T	Tt	T
	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Recycle: to Assembled circuit board(kg)
රි	Quantity	1.06E+01	1.38E-01	1.22E+02	8.52E-01	3.12E+00	9.66E+00	1.68E+01	1.67E+00
	Note								
	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
Consumables	Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Plastics(kg)
යි	Quantity	3.70E+00	4.89E-01	3.84E+01	1.85E+02	-1.22E+02	-8.52E-01	-3.12E+00	-9.66E+00
	Note								
	Classification	Deduction	Deduction	Distribution	Distribution				
Consumables	Distribution	Paper(kg)	Recycle: to Assembled circuit board(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
Ŝ	Quantity	-1.68E+01	-1.67E+00	1.86E+04	2.25E+04				
	Note								

6. Others

A.Product information:
All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included.

The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:
The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:

The power consumption is calculated assuming the use period of five years and 9,375,000 sheets printed during the use period according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.

The production impacts of the cartridges and toner used during the use period of five years are included.

The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years are included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

F.Disposal/Recycle stage information:
The information on the products recovered from users is included.
The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.