

Facsimile (PCR number: AH-03)



No. AH-18-E236 Date of publication Nov./30/2018



http://www.brother-usa.com/

For inquiry:

Environmental Product Group Production Innovation Dept. Quality, Production & Engineering Center

Brother Industries, Ltd. Tel: +81-52-824-2511(Representative) FAX: +81-52-824-5166




- Color Inkjet All-in-One **MFC-J5845DW** Specifications:
- Color Inkjet Printing
- Business Use
- Recording Paper Size: LDR (Max. 17 "x 11")
- Original Sheet Size: Max-width 11.7
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing
- Product weight: 16.75 kg

(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
 - Energy consumption 2,970MJ
- Global warming impact (CO₂ equivalent) 161.7kg
- Acidification impact (SO₂ equivalent) 0.233kg



- · Electric power consumption in 5 years of "Use stage" is 90.98kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, September 29, 2004,

Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025

Third party verifier *: System auditor, Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type ${\rm I\!I\!I}$ category.

Product Environmental Information Data Sheet (PEIDS)



Unit Function DB version

rization Factor DB version

Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-18-E236

PCR name	Facsimile		Product type		MFC-J5845DW		
PCR code	AH-03	Product weight (kg)	16.75	Package (kg)	3.43	Weight total (kg)	20.18

		_	_	Life Cycle Stage		Produ	uction				
In/O	ut iter	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Total
		-			MJ	1.66E+03	2.82E+02	5.63E+01	9.52E+02	2.15E+01	2.97E+03
		Er	nergy (Consumption	Mcal	3.97E+02	6.74E+01	1.35E+01	2.27E+02	5.15E+00	7.10E+02
	1		88	Coal	ka	7.01E+02	1.78E+00	1.32E-04	5.16E+00	1.31E-01	1.41E+01
			onic	Crude oil (for fuel)	ka	1.47E+01	2.10E+00	1.23E+00	6.34E+00	2.28E-01	2.46E+01
			Se la	LNG	kg	3.08E+00	8.94E-01	1.90E-02	2.62E+00	6.72E-02	6.68E+00
			nerg.	Uranium content of an ore	ka	2.52E-04	1.21E-04	8.92E-09	3.48E-04	8.84E-06	7.30E-04
	~		۵	Crude oil (for material)	ka	1.16E+01	1.08E-02	0	5.63E-04	0	1.22E+01
	ior			Iron content of an ore	kg	4.04E+00	0	0	3.25E-03	0	4.04E+00
	pt	es		Cu content of an ore	kg	2.02E-01	0	0	1.28E-05	0	2.02E-01
	L U	21		Al content of an ore	kg	5.91E-02	0	0	0	0	5.91E-02
	Su	NO I		Ni content of an ore	kg	1.28E-02	0	0	1.57E-03	0	1.44E-02
	ŭ	ree	se	C content of an ore	kg	1.86E-02	0	0	2.13E-03	0	2.07E-02
	e	<u>e</u>	DIN	Mn content of an ore	kg	2.04E-02	0	0	2.71E-04	0	2.07E-02
	n	stib	resources	Pb content of an ore	kg	7.87E-03	0	0	1.04E-06	0	7.87E-03
	so	aus		Sn content of an ore	kg	7.07L-03	-	-	1.042-00	-	1.07 2-03
	Impact by Resource Consumption	Exhaustible resources	a	Zn content of an ore	kg	- 7.75E-02	0	0	- 1.02E-05	0	7.75E-02
	Ś	ш	Mineral	Au content of an ore	kg	- -	-	-	1.02E-05 -	-	1.132-02
	풍		Ξ	Ag content of an ore	ka			-		-	
<i>(</i> 0	0a(Silica Sand	ka	7.42E-01	0	0	4.51E-05	0	7.43E-01
še	Ē			Halite	kg	6.82E-01	6.82E-05	0	4.21E-04	6.05E-03	6.89E-01
ai X	-			Limestone	kg	1.10E+00	2.36E-03	0	3.50E-02	1.83E-01	1.32E+00
ane				Natural soda ash	kg	7.64E-02	0	0	2.30E-02	0	7.64E-02
2			ł	Wood	ka	5.44E+00	3.07E-02	0	5.40E-00	0	6.01E+00
nventory anaiyses				Water	ka	6.18E+03	1.36E+03	9.93E-02	3.96E+03	1.11E+02	1.16E+04
en	÷	, ;		CO2	ka	7.65E+01	1.42E+01	4.00E+00	4.46E+01	1.97E+01	1.59E+02
È	Jer			Sox	ka	4.36E-02	1.07E-02	2.49E-03	3.28E-02	1.03E-02	9.98E-02
_	h		ere	Nox	ka	1.08E-01	8.85E-03	2.00E-02	3.19E-02	2.19E-02	1.91E-01
	<ir></ir>		ĥ	N2O	kg	8.15E-03	2.24E-04	6.57E-04	7.07E-02	2.82E-05	9.77E-03
	en		dsc	CH4	kg	6.74E-04	3.23E-04	2.38E-08	9.31E-04	2.37E-05	1.95E-03
	e		Atmosphere	CO	kg	8.46E-03	2.12E-04	5.41E-03	6.94E-03	3.97E-03	2.69E-02
	ott			NMVOC	kg	1.32E-03	6.32E-04	4.67E-08	1.82E-03	4.64E-05	3.82E-03
	Je t		9	CxHy	kg	3.82E-03	5.96E-05	5.87E-04	2.51E-04	7.25E-05	4.79E-03
	arc			Dust	kg	1.17E-02	4.73E-04	1.89E-03	1.88E-03	1.24E-03	1.72E-02
	Emission/Discharge to the environment	ε	.⊆	BOD	kg	-	-	-	-	-	1.122 02
	ä	to Water system	Water domain	COD	kg	-	-	-	-	-	
	/uo	r sy	r do	N total	ka	-	-	-	-	-	
	SSI	/ate	/ate	P total	ka	-	-	-	-	-	
	Ē	2	5	SS	ka	-	-	-	-	-	
		- 1	5	Unspecified Solid Waste	kg	7.63E-01	8.19E-04	0	4.10E-01	7.57E+00	8.75E+00
	Impact by		system	Slag	kg	1.31E+00	0	0	2.07E-03	0	1.31E+00
	oac		Soil s	Sludge	ka	2.64E-02	Ő	0	0	0	2.64E-02
	Ē		to S	Low level radio-active waste	ka	1.77E-04	8.43E-05	6.23E-09	2.43E-04	6.18E-06	5.10E-04
i c	~ s			Energy resources (crude oil equivalent)	ka	2.49E+01	5.31E+00	1.25E+00	1.56E+01	4.65E-01	4.76E+01
sme	by Res		Disease in the second sec	Mineral resources (Iron ore equivalent)	ka	6.23E+01	5.95E-03	0	1.56E+00	0	6.39E+01
ses			are	Global Warming (CO2 equivalent)	ka	7.87E+01	1.42E+01	4.18E+00	4.49E+01	1.97E+01	1.62E+02
ass	a de la companya de la company		sphe	Acidification (SO2 equivalent)	ka	1.19E-01	1.69E-02	1.65E-02	5.51E-02	2.56E-02	2.33E-01
Impact assessmen	m i Dechar		tmo								
l di	ty freing		to A								

[Notes for readers: EcoLeaf common rules]

. Stage related

A "Production" stage is intended for two sub-stages listed below

(1) "Raw material" production: consists of mining, transportation and raw material production (2) "Product" production: consists of the parts processing, assembly and installation,

B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage. C. Use' stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).

D. "Disposition" stage is intended for environmental impacts by product disposition.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value, e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel, C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system

IV Data entry forma

A. Exponential notation, after the decimal point to two, should be used.

B. Indicate "0" instead exponential indication, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
C. Indicate " - " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
D. Row total of the data is automatically calculated, excluding a row includes " - " item. Row total of such is presented as a blank (no data).

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. Product weight includes a toner cartridge, a drum unit and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.

In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery. 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.

The transportation distance in Japan uses 100 km as average distance.

4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48,000 sheets and printing 48,000 sheets by receiving.

- This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.
- It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days,

not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used. The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance. Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables. 5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines

6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-18-E236



	PCR name		Facsimile	(PCR ID:AH-03)	Product t	ype				MFC	J5845	5DW			
LCA	/LCIA in units of:		1		Product weig	ht (kg) 16.75 Pack		ackage (kg)	3.43		Weight total (kg)	20.18			
1. Prod	I. Product information (per unit): parts etc. by material and by process/assembly method														
		Bre	eakdown of pi	imary materials		Math I	breakdown of p	parts	, which need	to apply F	Processi	ing / Assembly Base Unit	ts (Parts B, C)		
	Material n	ame	Weight (kg)	Material name	Weight (kg)	F	Process nar	ne	Weig	ht (kg)	P	Process name	Weight (kg)		
	Steel		3.31E+00	Semiconductor substrate	7.02E-01	Press	Press molding:Iron (kg)		g) 3.39	E+00	Part	ts assembly (kg)	1.79E+00		
	Stainless steel		8.07E-02	Wood	6.07E-04	Press molding:Nonferrous metal (kg)		(kg) 1.16	E-02						
÷	Aluminum		1.16E-02	Medium-sized motor	5.31E-01	Injec	Injection molding (kg)		(g) 1.12	E+01					
oduct	Thermoplasti	c resin	1.20E+01	Lubricants	4.76E-03	Gla	ass molding	(kg) 7.03	E-01					
	Thermosettin	g resin	2.78E-02	Clean water	2.07E-01										
	Rubbe	r	6.24E-02												
	Glass		7.03E-01												
	Paper		2.54E+00												
	Subtota	al	1.87E+01	Subtotal	1.45E+00										
			Total		2.02E+01		Subtotal		1.53	E+01		Subtotal	1.79E+00		

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Energy
	Distribution	Polypropylene (kg)	Electricity (kWh)	Diesel truck:4 ton (kg·km)	Furnace urban gas (13A) (m3)	Gasoline as fuel (kg)	Freight by air (kg·km)	Freight by ship (kg·km)	Injection molding (kg)
ion	Quantity	1.09E-02	1.65E+01	9.92E-01	1.27E-03	2.83E-04	6.10E+01	6.50E+02	1.09E-02
Consumption	Note								
Inst	Classification	Material	Material	Energy	Energy	Energy	Energy	Energy	
Col	Distribution	Clean water (kg)	Corrugated cardboard (kg)	Diesel oil as fuel (kg)	Diesel truck:10 ton (kg·km)	Incineration: Industrial waste (kg)	Furnace LPG (kg)	Sewage processing (kg)	
	Quantity	5.49E+00	1.44E-02	1.11E-04	6.84E+01	3.64E-02	2.86E-02	5.48E+00	
	Note								
large	Classification								
Disch	Distribution								
Emission/	Quantity								
Emis	Note								
Note									

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck:20 ton (kg·km)	Freight by ship (kg·km)						
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
ution	Quantity	2.02E+01	1.05E+02	3.41E+01	6.21E+03	2.02E+01	3.00E+03	1.00E+02	6.05E+04
outi	Note								
Distribu	Means of transportation	Diesel truck:10 ton (kg·km)							
ä	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)				
	Quantity	2.02E+01	1.00E+02	3.39E+01	5.95E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 10 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 20 ton (kg.km)	Stainless steel plate (kg)	Low density polyethylene (kg)	PP (kg)	POM(polyacetal) (kg)
	Quantity	9.10E+01	2.30E+02	5.43E+03	2.41E+02	9.97E-03	4.42E-02	3.52E-01	3.28E-02
	Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	ABS (kg)	PET (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	Assembled circuit board(kg)	Clean water (kg)
	Quantity	1.01E-01	3.20E-04	2.64E-03	1.28E-01	1.05E-01	1.23E-02	9.28E-05	1.02E+00
Inc	Note								
Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
_	Distribution	Injection molding (kg)	Press molding: Iron (kg)	Parts assembly (kg)	Electricity (kwh)	Diesel truck: 10 ton (kg.km)	Freight by ship (kg.km)	Urban gas (m3)	Gasoline as fuel (kg)
	Quantity	5.33E-01	9.97E-03	4.42E-02	3.23E+00	3.19E+02	3.21E+03	6.25E-03	6.46E-05
	Note				Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years
	Classification	Consumption	Consumption	Process	Consumption	Consumption	Process	Process	
	Distribution	Diesel oil as fuel (kg)	LPG(NPG) as fuel (kg)	Clean water (kg)	PP (kg)	Injection molding (kg)	Incineration: Industrial waste (kg)	Sewage processing (kg)	
	Quantity	7.56E-05	6.54E-03	4.81E-01	5.36E-02	5.36E-02	9.06E-02	4.44E-01	
	Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	

Note Electric power consumption in 5 years of "Use stage" is 90.98kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

<u> </u>	Classification	Process	Process	Process	Process		
nab	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)		
Insu	Quantity	2.18E+02	1.95E+00	2.24E+00	1.51E-02		
Col	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected		

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

.0	Classification	Consumption	Process	Process	Process		
ari	Distribution	Diesel truck:4 ton (kg·km)	Shredding (kg)	Incineration to landfill(as ash) (kg)	Landfill:General waste (kg)		
cer	Quantity	1.91E+03	1.63E+01	1.44E+01	5.34E+00		
s	Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected		
Note							